






















Download

### 6011 safety coupling

Made of galvanized steel. We recommend using this coupling accessory when mounting the lamp near the joint of track 6001 to obtain greater mechanical safety.

Code	Kg	WTot	Colour
132907-00	0,13	0 W	WHITE

#### Prodotti

	- 6600 Techno System - 90°		- 6601 Techno System - 25°		- 6602 Techno System - 25° bi-		- 6603 Techno System - 30°x80°
	- 6604 Techno System - 60° wide-beam - CRI 90		- 6605 Techno System - wide-beam semi-spherical diffuser - CRI 90		- 6600 Techno System - 90° symmetric - CRI 80		- 6601 Techno System - 25° asymmetric - CRI 80
	- 6602 Techno System - 25° bi-asymmetric - CRI 80		- 6603 Techno System - 30°x80° elliptical - CRI 80		- 6606 Techno System HE - UGR - CRI 80		- 6605 Techno System - wide-beam - with semi-spherical diffuser - Ceiling
	- 6611 Techno System HE - 90° symmetric - CRI 80		- 6615 Techno System HE - 60° wide-beam - CRI 80		- 6614 Techno System HE - 30°x80° elliptical - CRI 80		- 6612 Techno System HE - 25° asymmetric - CRI 80
	- 6613 Techno System HE - 25°		- 6616 Techno System HE - wide-beam semi-spherical		- 6617 Techno System HE - 90°		

The reported luminous flux is the flux emitted by the light source with a tolerance of  $\pm 10\%$  compared to the indicated value. The W tot column indicates the total wattage absorbed by the system without exceeding 10% of the indicated