



## 773 Comfort T5 - high-gloss 99.99

Housing: In sheet steel.

Optics: Dark light double parabolic louvres, in high-gloss plated aluminium 99.99. Anti-dazzle and anti-iridescence, very low luminance. PVD treatment to increase light efficiency.

Painting: with polyester powder, UV-stabilized.

Lampholder: In polycarbonate, with contacts in phosphor bronze. Socket G13. Electric gear: 230V/50Hz power supply. Hard wire, 0.50 sq mm cross section and PVC-HT sheath resistant up to 90°, according to CEI 20-20 standards. 2P+T terminal block with maximum allowed lead cross section of 2.5 sq mm.

Equipment: 6.3A protection fuse

Standard supply: Snap fastening optics, which remain attached by safety cords.

Mounting: Ceiling or suspension.

Regulations: Produced according to applicable EN60598-1 CEI 34 - 21 standards, IP20IK07 degree of protection according to EN 60529 standards. They have obtained the ENEC European Certificate of Conformity. These products can be installed on normally inflammable surfaces.

Emergency light version: in maintained version. In the event of a "black out", one single lamp connected to the back-up circuit stays on. Run time 60 minutes. Sketch (see chapter).

Versions with 3-hour battery life upon request.

Download

Code	Gear	Kg	Lumen-K-CRI	WTot	Base	Colour
141013-00	CELL-F	4.21	FL 2x28-2650lm-4000K-Ra 1b	60 W	G5	WHITE
141011-09	CELLF-E	4.41	FL 1x49-4350lm-4000K-Ra 1b	59 W	G5	WHITE
141012-00	CELL-F	2.60	FL 2x14-1250lm-4000K-Ra 1b	31 W	G5	WHITE
141014-00	CELL-F	5.70	FL 2x49-4350lm-4000K-Ra 1b	105 W	G5	WHITE
141014-09	CELLF-E	6.20	FL 2x49-4350lm-4000K-Ra 1b	109 W	G5	WHITE
141018-00	CELL-F	3.94	FL 4x14-1250lm-4000K-Ra 1b	66 W	G5	WHITE
141019-09	CELLF-E	7.60	FL 4x28-2650lm-4000K-Ra 1b	124 W	G5	WHITE
141019-00	CELL-F	7.30	FL 4x28-2650lm-4000K-Ra 1b	120 W	G5	WHITE
141016-00	CELL-F	6.50	FL 3x28-2650lm-4000K-Ra 1b	88 W	G5	WHITE
141013-09	CELLF-E	4.50	FL 2x28-2650lm-4000K-Ra 1b	64 W	G5	WHITE
141011-00	CELL-F	3.70	FL 1x49-4350lm-4000K-Ra 1b	55 W	G5	WHITE
141016-09	CNRL-F	8.08	FL 3x28-2650lm-4000K-Ra 1b	92 W	G5	WHITE
141018-09	CELLF-E	4.44	FL 4x14-1250lm-4000K-Ra 1b	69 W	G5	WHITE
141010-09	CELLF-E	3.70	FL 1x28-2650lm-4000K-Ra 1b	34 W	G5	WHITE
141010-00	CELL-F	3.05	FL 1x28-2650lm-4000K-Ra 1b	30 W	G5	WHITE

### Accessories



- 2512 wire



- 2518 simple suspension

The reported luminous flux is the flux emitted by the light source with a tolerance of  $\pm 10\%$  compared to the indicated value. The W tot column indicates the total wattage absorbed by the system without exceeding 10% of the indicated