


## 858 Minicomfort T5 high-gloss 99.99



Housing: galvanized steel stove pre-enamelling.  
Louvre: Dark light Dark light double parabolic louvres, in high-gloss plated aluminium 99.99. Anti-dazzle and anti-iridescence, very low luminance. PVD treatment.

Lampholder: In polycarbonate, with contacts in phosphor bronze.

Electric gear: Automatic line and are 100% tested on the line 230V/50Hz electronic power supply. Hard wire, 0.50 sqmm cross section, and PVC-HT sheath, resistant up to 90°C, according to CEI 20-20 standards. 2P+T terminal block, with maximum allowed lead cross section of 2.5 sqmm.

Equipment: Quick connectors for electrical line and with door for electrical connections.

Snap fastening optics, which remain attached with nylon cords.

Anti-fingerprint gloves to avoid damage to the louvre during installation.

Mounting: Recessed for contact mounting on the cross T structure

Regulations: Produced according to applicable EN60598 CEI 34-21 standards, IP20IK07 degree of protection according to EN 60529. These products can be installed on normally inflammable surfaces.

Emergency light version: In maintained version. In the event of a black-out a single lamp connected to the back-up circuit continues to operate. Run time 60 minutes. On request: optional "Main Control System" available for emergency management.


Minimum size of hole for recessed installation:

Mini Comfort 4x14/3x14/2x14(600x600) = 572x572mm

Mini Comfort 2x14 = 572x270mm

Mini Comfort 4x28/3x28 = 1172x572mm

Mini Comfort 2x28 = 1172x270mm



Code	Gear	Kg	Watt	Base	Lamps	Colour
153421-07	CELL-E	0,00	FL 4x28	G5	2650lm-4000K-Ra 1b	-
153720-0041	CELL-D-D	3,00	FL 4x14	G5	1250lm-4000K-Ra 1b	WHITE
153720-07	CELL-E	2,85	FL 4x14	G5	1250lm-4000K-Ra 1b	WHITE
153720-51	CELL-DH	3,00	FL 4x14	G5	1250lm-4000K-Ra 1b	WHITE
153721-00	CELL	5,29	FL 4x28	G5	2650lm-4000K-Ra 1b	WHITE
153721-0041	CELL-D-D	7,80	FL 4x28	G5	2650lm-4000K-Ra 1b	WHITE
153721-51	CELL-DH	7,80	FL 4x28	G5	2650lm-4000K-Ra 1b	WHITE
153720-00	CELL	3,00	FL 4x14	G5	1250lm-4000K-Ra 1b	WHITE



### Download

DXF 2D

- 858.dxf

Montaggi

- 850-9\_minicomfort.pdf