

## 885 Compact

Recessed fixtures suitable for use with energy saving fluorescent lamps.  
 Housing: Pressed sheet steel.  
 Reflector: Polycarbonate; 100% aluminium powder coated through a P.V.D. hard-vacuum process; self-extinguishing; multi-faceted for greater light control and efficiency.  
 Coating: Anionic electrocoating in acrylic white lacquer, UV-stabilised  
 Lampholder: PBT with phosphor bronze contacts (FLC).  
 Electric gear: 230V/50Hz power supply. Hard wire, 0.50 sqmm cross section and heat-resistant (90°C) PVC-HT sheath, in accordance with CEI 20-20 standards. 2P+T terminal block (maximum allowed lead cross section 2.5 sqmm.). Discharge lamp versions are equipped with thermal protection.  
 Regulations: Manufactured in accordance with standards EN60598 – CEI 34 –21. Degree of protection in accordance with standards EN60529.



**Download**  
 Montaggi  
 - compact.pdf

Code	Gear	Kg	Lumen-K-CRI	WTot	Base	Colour
156432-08	CELL	2.50	FLC 2x18D/E-1200lm-4000K-Ra 1b	37 W	G24q-2	BIANCO
156433-09	CELL-E	3.50	FLC 2x26D/E-1800lm-4000K-Ra 1b	56 W	G24q-3	BIANCO
156433-08	CELL	2.50	FLC 2x26D/E-1800lm-4000K-Ra 1b	53 W	G24q-3	BIANCO
156432-09	CELL-E	2.50	FLC 2x18D/E-1200lm-4000K-Ra 1b	40 W	G24q-2	BIANCO

The reported luminous flux is the flux emitted by the light source with a tolerance of  $\pm 10\%$  compared to the indicated value. The W tot column indicates the total wattage absorbed by the system without exceeding 10% of the indicated