


828 Comfort - prismatic diffuser



HOUSING and CHASSIS: stainless steel sheeting with narrow rim.
SHIELD: prismatic polycarbonate flat sheeting.
FRAME: coated sheeting.
COATING: white polyester powder coating, UV stabilized, and anti-yellowing with phosphate pre-treatment.
LAMP HOLDER: in polycarbonate and contactors in phosphorous bronze. G13 connector.
WIRING: 230V/50Hz power supply. Rigid cable with cross-section of 0.50 mm² and PVC-HT sheathing resistant to 90 °C pursuant to CEI 20-20 standards 2P+T terminal block with conductors having maximum cross-section of 2.5 mm².
MOUNTING: recessed into shooks or 600 module panels.
EQUIPMENT: complete with brackets for the installation on T-beams of false ceilings.
STANDARDS: compliant with EN60598-1 CEI 34-21 standards, IP54IK07 protection according to EN 60529 standards, certified by the Brand Quality Institute (IMQ) and the ENEC European mark for electrical products. Suitable for installation on normally inflammable surfaces.
OTHER WIRING: electronic ballast.
EMERGENCY VERSION: in the event of a blackout, only one of the lamps connected to the emergency circuit will remain fully operational, thus avoiding the inconvenience and possible hazards caused by sudden power failure. Battery life is 60 min. Once power is restored, the battery will automatically recharge.



Download

DXF 2D
 - d827.dxf
 - d827.dxf

3DS
 - 825_2x36.3ds

3DM
 - 825_2x36.3dm

Montaggi
 - bs_p_ap.dxf
 - appog_d.dxf

Code	Gear	Kg	Lumen-K-CRI	WTot	Base	Colour
156825-08	CEL-F	8.20	FL 2x36-3350lm-4000K-Ra 1b	70 W	G13	WHITE
156829-08	CEL-F	13.00	FL 4x36-3350lm-4000K-Ra 1b	146 W	G13	WHITE
156825-12	CELF-D	8.20	FL 2x36-3350lm-4000K-Ra 1b	74 W	G13	WHITE
156824-08	CEL-F	4.83	FL 2x18-1350lm-4000K-Ra 1b	38 W	G13	WHITE
156828-12	CELF-D	7.37	FL 4x18-1350lm-4000K-Ra 1b	76 W	G13	WHITE
156824-12	CELF-D	4.83	FL 2x18-1350lm-4000K-Ra 1b	37 W	G13	WHITE
156822-00	CELL-F	7.10	FL 4x14-1250lm-4000K-Ra 1b	66 W	G5	WHITE
156829-12	CELF-D	12.92	FL 4x36-3350lm-4000K-Ra 1b	142 W	G13	WHITE
156828-08	CEL-F	8.69	FL 4x18-1350lm-4000K-Ra 1b	73 W	G13	WHITE

The reported luminous flux is the flux emitted by the light source with a tolerance of $\pm 10\%$ compared to the indicated value. The W tot column indicates the total wattage absorbed by the system without exceeding 10% of the indicated