



992 EL Eterna - protection "nA" + "tc"

HOUSING: AISI 304 18/8 stainless steel drawn in a single piece with high mechanical resistance;
 FRAME: AISI 304 18/8 stainless steel with safety screws for protection against accidental opening;
 LATCHES: AISI 304 18/8 stainless steel with safety screws for protection against accidental opening;
 REFLECTOR: high-gloss 99.85 aluminium, large size for higher efficiency;
 DIFFUSER: 5mm thick tempered glass, resistant to impact and thermal shock;
 GASKETS: All the gaskets are retained and made of silicone rubber resistant to low and high temperatures;
 CABLE GLAND: Impact resistant metal, for environments at risk of explosion according to CEI EN 50014 with working temperatures ranging between -30°C and +90°C ;
 ELECTRONIC BALLAST: cathode preheating, thermal protection and energy efficiency class A2;
 INTERNAL ELECTRIC GEAR: single-pole PVC cable with 0.5sqmm cross section, heat resistant at 90°C;
 POWER SUPPLY TERMINAL: Two poles + grounding with 2.5sqmm maximum lead cross section;

Download

Montaggi
 - eterna_cel_atex.pdf

Code	Gear	Kg	Lumen-K-CRI	WTot	Base	Colour
162374-00	CEL-F	11.80	FL 2x36-3350lm-4000K-Ra 1b	72 W	G13	STAINLESS STEEL
162373-00	CEL-F	6.90	FL 2x18-1350lm-4000K-Ra 1b	38 W	G13	STAINLESS STEEL
162377-00	CEL-F	12.90	FL 3x36-3350lm-4000K-Ra 1b	108 W	G13	STAINLESS STEEL
162378-00	CEL-F	12.71	FL 3x58-5200lm-4000K-Ra 1b	165 W	G13	STAINLESS STEEL
162375-00	CEL-F	14.00	FL 2x58-5200lm-4000K-Ra 1b	110 W	G13	STAINLESS STEEL

Accessories



- 945 - narrow beam 2-lamp reflector

The reported luminous flux is the flux emitted by the light source with a tolerance of ± 10% compared to the indicated value. The W tot column indicates the total wattage absorbed by the system without exceeding 10% of the indicated