



Download






















## Recessed springs

acc. 22001491-00 - 295x595 - 295x295 - 595x595  
 acc. 22001492-00 - 295x1185 Ideal for mounting the fixture in plasterboard false ceilings.

Code	Kg	WTot	Colour
22001491-00	0,19	0 W	STEEL
22001492-00	0,25	0 W	STEEL

### Prodotti

 - PanelTech UGR<19 - A	 - Pannello B	 - PanelTech High Performance -	 - Eco Pannello luminoso
 - PanelTech UGR<19 - B	 - PanelTech UGR<19 - R2	 - PanelTech UGR<19 - R3	 - Eco Pannello luminoso R2
 - PanelTech - PUSH DALI - UGR<19	 - Eco Pannello luminoso - CAM	 - Eco Pannello luminoso R2 - CAM	 - Eco Pannello luminoso R4
 - PanelTech High Performance - UGR<19 - A2 - CAM	 - PanelTech High Performance - UGR<19 - R2 - CAM	 - Pannello B - R2	 - PanelTech High Performance - UGR<19 - R2
 - Eco Pannello luminoso - architectural	 - Eco Pannello luminoso 2x2 - UGR<19	 - Eco Pannello luminoso 2x2	

The reported luminous flux is the flux emitted by the light source with a tolerance of  $\pm 10\%$  compared to the indicated value. The W tot column indicates the total wattage absorbed by the system without exceeding 10% of the indicated