



Sintesi System - suspension direct/indirect light - Dark light - UGR<19

Sintesi System is the new linear lighting system by Fosnova with a sober and elegant design, available in a wide range of optics and LED modules. The system can be easily mounted as a suspension lamp for direct and/or indirect lighting, as a ceiling lamp or in continuous lines, making it the most effective choice for any lighting project and obtain the needed lighting level with an efficient use of energy. Housing: in extruded 6060 aluminium alloy. Removable top cover in extruded 6060 aluminium for electrical connection. Closing ends: V0 ABS plastic injection moulded. LED: Luminous flux maintenance 80%: 50.000h (L80B20). Power factor 0,92. Dark light louvre: double parabolic louvres, in high-gloss 99.99 aluminium, anti-glare and anti-iridescence, very low luminance with PVD treatment or in double parabolic louvres, in high-gloss 99.85 aluminium. Regulations: Manufactured in accordance with standards EN60598 – CEI 34 –21. Degree of protection in accordance with standards EN60529.

-
-
-
-
-
-
-
-
-
-
-
-
-
-
-
-
-
-
-
-

Download
 DXF 2D
 - sintesisosp.dxf
 Montaggi
 - SINTESI-SYSTEM REV3.pdf

Code	Gear	Kg	Lumen Output-K-CRI	WTot	Colour
22010016-00	CLD	3.04	LED-3693lm-4000K-CRI 80	40 W	WHITE
22010016-1241	CLD-D-D	3.17	LED-3693lm-4000K-CRI 80	40 W	WHITE
22010016-39	CLD	3.04	LED-3434lm-3000K-CRI 80	40 W	WHITE
22010016-3941	CLD-D-D	3.18	LED-3434lm-3000K-CRI 80	40 W	WHITE
22010017-00	CLD	5.85	LED-7386lm-4000K-CRI 80	76 W	WHITE
22010017-1241	CLD-D-D	5.89	LED-7386lm-4000K-CRI 80	76 W	WHITE
22010016-09	CLD CELL-E	0.00		35 W	WHITE
22010017-09	CLD-E	3.69	LED-7386lm-4000K-CRI 80	76 W	WHITE
22010017-39	CLD	5.86	LED-6869lm-3000K-CRI 80	76 W	WHITE
22010017-3941	CLD CELL-D-D	0.00	LED-6869lm-3000K-CRI 80	76 W	WHITE
22010018-00	CLD	8.50	LED-11079lm-4000K-CRI 80	108 W	WHITE
22010018-1241	CLD-D-D	8.65	LED-11079lm-4000K-CRI 80	108 W	WHITE
22010018-09	CLD-E	3.69	LED-11079lm-4000K-CRI 80	108 W	WHITE
22010018-39	CLD CELL	0.00	LED-10303lm-3000K-CRI 80	108 W	WHITE
22010018-3941	CLD CELL-D-D	0.00	LED-10303lm-3000K-CRI 80	108 W	WHITE

Accessories

- Ceiling suspension
- Ceiling suspension
- Powered suspension 3-5 p
- Ceiling suspension Q
- Powered suspension Q
- Closing ends 1 - Sintesi
- Sintesi Sensor - light and/or presence detector
- Sintesi Spot - UGR<22 - light module
- Connecting bracket - Sintesi
- Suspension with rods Q
- Powered suspension with rods Q

The reported luminous flux is the flux emitted by the light source with a tolerance of ± 10% compared to the indicated value. The W tot column indicates the total wattage absorbed by the system without exceeding 10% of the indicated