



## Sintesi System - suspension direct/indirect light - with matt shield - UGR<22

Sintesi System is the new linear lighting system by Fosnova with a sober and elegant design, available in a wide range of optics and LED modules. The system can be easily mounted as a suspension lamp for direct and/or indirect lighting, as a ceiling lamp or in continuous lines, making it the most effective choice for any lighting project and obtain the needed lighting level with an efficient use of energy. Housing: in extruded 6060 aluminium alloy. Removable top cover in extruded 6060 aluminium for electrical connection. Closing ends: V0 ABS plastic injection moulded. LED: Luminous flux maintenance 80%: 50.000h (L80B20). Power factor 0,92. Diffuser: shield in transparent PMMA with high-performance wide-beam matt film. Regulations: Manufactured in accordance with standards EN60598 – CEI 34 –21. Degree of protection in accordance with standards EN60529.

- 
- 
- 
- 
- 
- 
- 
- 
- 
- 
- 
- 
- 
- 
- 
- 
- 
- 
- 
- 

**Download**  
 DXF 2D  
 - sintesisosp.dxf  
 Montaggi  
 - SINTESI-SYSTEM REV3.pdf

Code	Gear	Kg	Lumen Output-K-CRI	WTot	Colour
22010216-00	CLD	3.55	LED-3924lm-4000K-CRI 80	40 W	WHITE
22010216-09	CLD CELL-E	0.00		35 W	WHITE
22010216-1241	CLD-D-D	3.69	LED-3924lm-4000K-CRI 80	40 W	WHITE
22010216-39	CLD	3.51	LED-3649lm-3000K-CRI 80	40 W	WHITE
22010216-3941	CLD-D-D	3.68	LED-3649lm-3000K-CRI 80	40 W	WHITE
22010217-00	CLD	6.79	LED-7848lm-4000K-CRI 80	76 W	WHITE
22010217-1241	CLD-D-D	6.82	LED-7848lm-4000K-CRI 80	76 W	WHITE
22010217-09	CLD-E	3.69	LED-7848lm-4000K-CRI 80	76 W	WHITE
22010217-39	CLD	6.75	LED-7299lm-3000K-CRI 80	76 W	WHITE
22010217-3941	CLD-D-D	6.98	LED-7299lm-3000K-CRI 80	76 W	WHITE
22010218-00	CLD	3.69	LED-11772lm-4000K-CRI 80	108 W	WHITE
22010218-1241	CLD-D-D	9.90	LED-11772lm-4000K-CRI 80	108 W	WHITE
22010218-09	CLD-E	3.69	LED-11772lm-4000K-CRI 80	108 W	WHITE
22010218-39	CLD	9.85	LED-10948lm-3000K-CRI 80	108 W	WHITE
22010218-3941	CLD-D-D	10.20	LED-10948lm-4000K-CRI 80	108 W	WHITE

### Accessories

- Ceiling suspension
- Ceiling suspension
- Powered suspension 3-5 p
- Ceiling suspension Q
- Powered suspension Q
- Closing ends 1 - Sintesi
- Sintesi Sensor - light and/or presence detector
- Sintesi Spot - UGR<22 - light module
- Connecting bracket - Sintesi
- Suspension with rods Q
- Powered suspension with rods Q

The reported luminous flux is the flux emitted by the light source with a tolerance of ± 10% compared to the indicated value. The W tot column indicates the total wattage absorbed by the system without exceeding 10% of the indicated