



Download DXF 2D - microfood.dxf





Micro Liset HO - FRUIT

Highlighting the freshness, colours and appearance of the foods on display is fundamental to improve the shopping experience and increase the customer's purchase intention. The LED sources especially designed for the FOOD sector combined with the fixtures manufactured by Fosnova are the best solution to effectively illuminate the foods on display, such as: MEAT, FISH, FRUIT, VEGETABLES, CHEESE, BREAD AND PASTRY.

The main features of this new technology can be summarised as follows: • HIGH COLOUR RENDERING • VERY LOW UV RAY OUTPUT • COLOUR TEMPERATURE (K) • DEDICATED EMISSION SPECTRUM • REMARKABLE ENERGY SAVING

Housing: made of oxidized extruded aluminium.

Diffuser: made of clear polycarbonate,

Regulations: Manufactured in accordance with standards EN60598 – CEI 34 –21. Degree of protection in accordance with standards EN60529. Use transformer acc. 22092022-00 (MAX 70W) or 22090839-00 (MAX 20W).

DIM 22090840-00 (MAX 20W).

Photobiological safety class: exempt group EN62471.



| Code          | Gear    | Kg   | Lumen Output-K-CRI            | WTot | Colour    |
|---------------|---------|------|-------------------------------|------|-----------|
| 22014773-0035 | CLD S+L | 0,00 | LED 18x0,4W white3000K-CRI 91 | 7 W  | ALUMINIUM |
| 22014774-0035 | CLD S+L | 0,00 | LED 24x0,4W white3000K-CRI 91 | 10 W | ALUMINIUM |
| 22014775-0035 | CLD S+L | 0,00 | LED 36x0,4W white3000K-CRI 91 | 14 W | ALUMINIUM |

Accessor



- Bracket - Microliset

- IP20 Microliset box

- Dimmable power supply

ıpply



- Profile for Microliset

The reported luminous flux is the flux emitted by the light source with a tolerance of  $\pm$  10% compared to the indicated value. The W tot column indicates the total wattage absorbed by the system without exceeding 10% of the indicated