



Pastilla - 100/240 V

Pastilla is a high-efficiency LED fixture, an ideal upgrade solution to traditional lamps. Its simple yet modern design, along with the supplied bracket, ensures quick installation into different spaces, including corridors, stairways, bathrooms, entrance halls or public areas. It is available in three diameter sizes (ø220/280/330 mm) and in the standard 3000K/4000K version, or with light-presence detectors (ON-OFF) on request. Housing: vandal-resistant, self-extinguishing polycarbonate. Diffuser: In clear polycarbonate, anti-dazzle, vandal resistant. LED: Luminous flux maintenance 70% 30.000h (L70B50). Power factor >0.9.

Download

DXF 2D

- past.dxf

Montaggi

- PASTILLA rev4.pdf

BIM

- Pastilla - 100-240 V - 20201005.zip

Code	Gear	Kg	Lumen Output-K-CRI	WTot	Colour
22042510-00	CLD	0,53	LED-1328lm-3000K-CRI 80	15 W	WHITE
22042511-00	CLD	0,55	LED-1444lm-4000K-CRI 80	15 W	WHITE
22042512-00	CLD	0,77	LED-1651lm-3000K-CRI 80	18 W	WHITE
22042513-00	CLD	0,79	LED-1796lm-4000K-CRI 80	18 W	WHITE
22042514-00	CLD	1,01	LED-2273lm-3000K-CRI 80	24 W	WHITE
22042515-00	CLD	1,02	LED-2473lm-4000K-CRI 80	24 W	WHITE
22042512-19	CLD	0,83	LED-1651lm-3000K-CRI 80	18 W	WHITE
22042513-19	CLD	0,83	LED-1796lm-4000K-CRI 80	18 W	WHITE
22042514-19	CLD	1,05	LED-2273lm-3000K-CRI 80	24 W	WHITE
22042515-19	CLD	1,08	LED-2473lm-4000K-CRI 80	24 W	WHITE
22042510-0050	CLD-EC	0,53	LED-1328lm-3000K-CRI 80	15 W	WHITE
22042511-0050	CLD-EC	0,53	LED-1444lm-4000K-CRI 80	15 W	WHITE
22042512-0050	CLD-EC	0,89	LED-1651lm-3000K-CRI 80	18 W	WHITE
22042513-0050	CLD-EC	0,80	LED-1796lm-4000K-CRI 80	18 W	WHITE
22042514-0050	CLD-EC	1,10	LED-2273lm-3000K-CRI 80	24 W	WHITE
22042515-0050	CLD-EC	1,01	LED-2473lm-4000K-CRI 80	24 W	WHITE

The reported luminous flux is the flux emitted by the light source with a tolerance of ± 10% compared to the indicated value. The W tot column indicates the total wattage absorbed by the system without exceeding 10% of the indicated