



**Download**  
 Montaggi  
 - FASHION REV3.pdf



## Fashion R3 with optics

Colour is a key factor in enticing consumers to buy. Therefore the lighting of points of sale must improve the viewing of the wares on display. This result can be obtained only with wide-beam light sources capable of ensuring a correct viewing of colours.

Fashion is created to satisfy the lighting needs of showrooms and every other space requiring accent lighting.

Housing: in die-cast aluminium.

Version with reflector: in die-cast polished aluminium, high efficiency and anti-glare.

Coating: power-coated with a UV-resistant polyester epoxy paint.

Regulations: Manufactured in accordance with EN 60598-1-CEI 34.21 standards. Degrees of protection in accordance with EN60529 standards.

Luminous flux maintenance L80B20: 50.000h. Power factor >0.9

Photobiological safety class: Exempt group

DALI dimmable version -1241 to be used with OMNITRACK PLUS track-mounted system.

Code	Gear	Kg	Lumen Output-K-CRI	WTot	Colour
22044410-00	CLD	0.68	LED COB-2846lm-3000K-34°-CRI>90	30 W	WHITE
22044411-00	CLD	0.69	LED COB-3060lm-4000K-34°-CRI>90	30 W	WHITE
22044430-00	CLD	0.68	LED COB-2846lm-3000K-34°-CRI>90	30 W	BLACK
22044431-00	CLD	0.68	LED COB-3060lm-4000K-34°-CRI>90	30 W	BLACK
22044410-1241	CLD-D-D	0.68	LED COB-2846lm-3000K-34°-CRI>90	30 W	WHITE
22044411-1241	CLD-D-D	0.69	LED COB-3060lm-4000K-34°-CRI>90	30 W	WHITE
22044430-1241	CLD-D-D	0.80	LED COB-2846lm-3000K-34°-CRI>90	30 W	BLACK
22044431-1241	CLD-D-D	0.68	LED COB-3060lm-4000K-34°-CRI>90	30 W	BLACK

The reported luminous flux is the flux emitted by the light source with a tolerance of ± 10% compared to the indicated value. The W tot column indicates the total wattage absorbed by the system without exceeding 10% of the indicated