



## Domitilla

Housing: in steel, complete with DIMM power cable.

Diffuser: opal polycarbonate.

Equipment: complete with push-button on the cable and plug-in power supply to be connected directly to the power socket.

LED: luminous flux maintenance 80%: 50.000h (L80B20).

### Download

DXF 2D  
- domi.dxf



Code	Gear	Kg	Lumen Output-K-CRI	WTot	Colour
22051010-00	CLD CELL	2,70	LED-630lm-4000K-CRI>90	0 W	WHITE
22051010-39	CLD CELL	2,70	LED-588lm-3000K-CRI>90	0 W	WHITE
22051030-00	CLD CELL	2,70	LED-630lm-4000K-CRI>90	0 W	BLACK
22051030-39	CLD CELL	2,70	LED-588lm-3000K-CRI>90	0 W	BLACK
22051070-00	CLD CELL	2,70	LED-630lm-4000K-CRI>90	0 W	GRAPHITE
22051070-39	CLD CELL	2,70	LED-588lm-3000K-CRI>90	0 W	GRAPHITE

The reported luminous flux is the flux emitted by the light source with a tolerance of  $\pm 10\%$  compared to the indicated value. The W tot column indicates the total wattage absorbed by the system without exceeding 10% of the indicated