

























Œ	$\overline{\mathbb{V}}$	
	•	

Code	Gear	Kg	Colour	Dimensions	W Tot	lamp
22062710-00	CLD CELL	0.30	white	0x0x120 Ø105	7	POWERLED 7W-GU10-450lm-3000K - 25°
22062760-00	CLD CELL	0.30	chrome	0x0x120 Ø105	7	POWERLED 7W-GU10-450lm-3000K - 25°
22062770-00	CLD CELL	0.30	met. silver	0x0x120 Ø105	7	POWERLED 7W-GU10-450lm-3000K - 25°
22062780-00	CLD CELL	0.30	Gold	0x0x120 Ø105	7	POWERLED 7W-GU10-450lm-3000K - 25°

These adjustable recessed spotlights, of moderate height, are ideal for installation in low false ceilings or display shelves, and are extremely easy to install.

Housing: Die-cast zamak, with a steel bracket holding the terminal block. Includes springs for recessed mounting.

Coating: Humidity-resistant acrylic-resin liquid paint, UV-stabilised, . A different galvanic finishing process is used for chromium-plated and polished brass versions.

Regulations: Manufactured in accordance with standards EN60598 - 1 - CEI 34.21. Degree of protection in accordance with standards EN60529.

09/09/2014 P. 1 / 1 File: 6.4 - Year 2014