



STOP 23 (\$340° 45°)

"Ifosnova









Code	Gear	Kg	Colour	Dimensions	lamp
22063012-00	CLD S+L	0.30	white	0x0x120 Ø102	POWERLED white-650lm-3000K-25°
22063073-00	CLD S+L	0.30	met. silver	0x0x120 Ø102	POWERLED white-650lm-3000K-25°
22063064-00	CLD S+L	0.30	chrome	0x0x120 Ø102	POWERLED white-650lm-3000K-25°
22063095-00	CLD S+L	0.30	Gold	0x0x120 Ø102	POWERLED white-650lm-3000K-25°

These adjustable recessed spotlights, of moderate height, are ideal for installation in low false ceilings or display shelves, and are extremely easy to install.

Housing: Die-cast zamak, with a steel bracket holding the terminal block. Includes springs for recessed mounting.

Coating: Humidity-resistant acrylic-resin liquid paint, UV-stabilised, . A different galvanic finishing process is used for chromium-plated and polished brass versions.

Electric gear: Transformer to be purchased separately.

Regulations: Manufactured in accordance with standards EN60598 - 1 - CEI 34.21. Degree of protection in accordance with standards EN60529.

Complete with 1 module PowerLed 3X2.5w - 4000K - 650lm@700mA - 25°

Separate transformer required (code 22090837-00 max 4 spot - 350mA)

10/06/2014 File: 6.4 - Year 2014 P. 1 / 1