


Themis L150 - fixed with lens

Themis stands out for its simple design and high-quality lighting output delivered by latest generation LED sources. Studied to deliver direct lighting, it is equipped with a highly efficient reflector (adjustable) or with lenses to enhance the light beam. Designed to be easily installed inside ceilings thanks to its mounting bracket, it is capable of illuminating full and empty spaces, bringing out all the potential of architectural details and giving rhythm and colour to important interiors. Housing: made of die-cast aluminium with clear polycarbonate diffuser. Equipment: supplied with bracket for ceiling installation. Reflector: high-efficiency metallised polycarbonate. LED: Luminous flux maintenance 80%: 50.000h (L80B20). Power factor >0.9. Photobiological safety class: exempt group EN62471.



| Code | Gear | Kg | Lumen Output-K-CRI | WTot | Colour |
|---------------|------------|------|---------------------------------|------|--------|
| 22071510-00 | CLD | 0,84 | LED COB-2442lm-3000K-24°-CRI 85 | 25 W | WHITE |
| 22071510-1241 | CLD CELLDD | 0,80 | LED COB-2442lm-3000K-24°-CRI 85 | 25 W | WHITE |
| 22071570-00 | CLD | 0,82 | LED COB-2442lm-3000K-24°-CRI 85 | 25 W | GREY |
| 22071570-1241 | CLD CELLDD | 0,80 | LED COB-2442lm-3000K-24°-CRI 85 | 25 W | GREY |



Download

DXF 2D
- them150L.dxf

Montaggi
- THEMIS_PLA rev3.pdf

The reported luminous flux is the flux emitted by the light source with a tolerance of $\pm 10\%$ compared to the indicated value. The W tot column indicates the total wattage absorbed by the system without exceeding 10% of the indicated