

### Power supply series 24VDC 220-240V 50/60Hz

- Version constant current for Power LED - Screw terminals 1.5 mm<sup>2</sup> - Short circuit protection, overload, open circuit and thermal - High performance with minimum heat loss and absolute reliability - Compliance with EN61347-2-13 EN61347-1, EN62384, EN55015, EN61000-3-2, EN61547

Download

Code	Gear	Kg	Lumen-K-CRI	WTot
22090893-00	CLD	0,10		17 W
22090839-00	CLD	0,08	220-240V-24vDC 20W---	20 W
22092022-00	CLD	0,30		70 W

#### Prodotti



- Micro Liset - 4000K - CRI 80



- Micro Liset - IP65



- Micro Liset opal - 3000K - CRI



- Micro Liset - for solid line -



- Minilinea LED - wall version



- Micro Liset HO - 3000K - CRI 80



- Micro Liset - 3000K - CRI 92



- Micro Liset HO - 4000K - CRI 80



- Micro Liset - for solid line - 3000K - CRI 92



- Micro Liset TT



- Micro Liset HO - MEAT



- Micro Liset HO - BREAD



- Micro Liset HO - CHEESE



- Micro Liset HO - FRUIT



- Micro Liset HO - FISH



- Aosta LED



- Micro Liset HO - 6500K - CRI 80

The reported luminous flux is the flux emitted by the light source with a tolerance of  $\pm 10\%$  compared to the indicated value. The W tot column indicates the total wattage absorbed by the system without exceeding 10% of the indicated