


Download

DXF 2D
- trim111b2.dxf
Montaggi
- TRIMLESS-B_50-70-111 rev3.pdf



Trimless 111 - B2

Housing: in die-cast aluminium with adjustable and tilting spotlights.
Equipment: equipped with galvanised steel support brackets which guarantee perfect attachment to suspended ceiling from 12 mm to 25 mm thick.
Reflector: high-efficiency metallised polycarbonate. Regulations: Manufactured in accordance with standards EN60598 – CEI 34 –21. Degree of protection in accordance with standards EN60529.
LED: High-efficiency light sources (CRI 90).
Power factor: ≥ 0.95
Photobiological safety class: Exempt group.
Luminous flux maintenance 80%: 50.000h (L80B20).
recessed Ø 315x168mm



Code	Gear	Kg	Lumen Output-K-CRI	WTot	Colour
22111210-00	CLD	1,70	LED COB2x-3089lm-3000K-15°-CRI 90	76 W	WHITE
22111210-1241	CLD CELLDD	1,70	LED COB2x-3089lm-3000K-15°-CRI 90	80 W	WHITE
22111211-00	CLD	1,70	LED COB2x-3322lm-4000K-15°-CRI 90	76 W	WHITE
22111211-1241	CLD CELLDD	1,70	LED COB2x-3322lm-4000K-15°-CRI 90	80 W	WHITE
22111212-00	CLD	1,70	LED COB2x-3029lm-3000K-25°-CRI 90	76 W	WHITE
22111212-1241	CLD CELLDD	1,70	LED COB2x-3029lm-3000K-25°-CRI 90	80 W	WHITE
22111213-00	CLD	1,70	LED COB2x-3257lm-4000K-25°-CRI 90	76 W	WHITE
22111213-1241	CLD CELLDD	1,70	LED COB2x-3257lm-4000K-25°-CRI 90	80 W	WHITE
22111214-00	CLD	3,10	LED COB2x-2988lm-3000K-40°-CRI 90	76 W	WHITE
22111214-1241	CLD CELLDD	1,70	LED COB2x-2988lm-3000K-40°-CRI 90	80 W	WHITE
22111215-00	CLD	3,10	LED COB2x-3213lm-4000K-40°-CRI 90	76 W	WHITE
22111215-1241	CLD CELLDD	1,70	LED COB2x-3213lm-4000K-40°-CRI 90	80 W	WHITE

The reported luminous flux is the flux emitted by the light source with a tolerance of $\pm 10\%$ compared to the indicated value. The W tot column indicates the total wattage absorbed by the system without exceeding 10% of the indicated