




## Download

DXF 2D self4.dxf Montaggi self1-2-3-4.pdf





## Self 4 - DIMM

Using light as an interior design element Over the past few years, interior lighting design has completely changed the way we decorate our home environments. The primary objective of interior lighting design is to achieve maximum visual comfort that takes on different meanings based on the context in which the lighting fixture is mounted. In the retail sector, from large shopping centres to small shops, lighting is the central element around which the right system should be designed in order to create a pleasant and attractive environment for customers. The great versatility of our new spotlights enhances the merchandise in the best way possible and creates customised lighting systems to make the brand always recognisable. In the hospitality and leisure sector (hotels, bars, restaurants) lighting is equally important to create a customised and well recognisable style. Fosnova, the ideal supplier for any type of customer, offers a wide range of spotlights and other lighting solutions to meet the needs of any type of environment. In homes, together with decorative lamps, recessed spotlights can supplement the lighting system with striking effects that can be controlled with advanced light control systems. The right light in the right place Today, LED can achieve a wide variety of colours and performance levels, returning a product to its true colour. It is however, up to the designer to decide upon the right colour temperature that, in addition to the LED source, can enhance the yellows and reds, or the different shades of light and dark blue. The lighting designer is now aware of the fact that the right selection of the whole system, as well as the fixture's design the reflection engine and the entremative adduct the reserver. design, the reflector's opening angle, the appropriate colour temperature and CRI value are fundamental to guarantee a store's success and increase sales. The right lighting and fixture play a vital role in facilitating sales. This is the reason why LED fixtures with a CRI above 90 are being requested. Therefore, the current trend is geared towards the manufacturing of more flexible fixtures, which also emit an excellent quality of light, while guaranteeing remarkable energy savings and lower maintenance costs. Fosnova has

designed a line of recessed spotlights suited to meet all these needs. Housing: fixed donwlight in die cast aluminium complete with spring clips for recessed mounting

Reflector: dark light optics in white colour, anti-glare aluminium to optimise light efficiency. Installation: Self LED is equipped with galvanised steel support brackets, with housing for springs for attachment to the false ceilings.

Painting: dust painted, using polyester epoxy paint to withstand UV rays

Standard supply: Includes adjustable steel bracket. Regulations: Manufactured in accordance with standards EN60598 - CEI 34 -21. Degree

 LED:
 3600lm
 42W
 3000K
 CRI 90
 38°
 - DIM 0/10V UGR<19</td>

 LED:
 3600lm
 42W
 3000K
 CRI 90
 - 38°
 - DIM 0/10V UGR<19</td>

 LED:
 3600lm
 42W
 3000K
 CRI 90
 - 60°
 - DIM 0/10V

 LED:
 3600lm
 42W
 3000K
 CRI 90
 - 60°
 - DIM 0/10V

 LED:
 3600lm
 51W
 3000K
 CRI 90
 - 38°
 - DIM 0/10V

 LED:
 4500lm
 51W
 3000K
 CRI 90
 - 60°
 - DIM 0/10V

 LED:
 4500lm
 51W
 3000K
 CRI 90
 - 60°
 - DIM 0/10V

 LED:
 4500lm
 51W
 3000K
 CRI 90
 - 60°
 - DIM 0/10V

LED: 4500lm - 51W - 3000K - CRI 90 - 90° - DIM 0/10V Power factor: 0.9

Power racio: 0.7 Photobiological safety class: Exempt group. Luminous flux maintenance 70%: 50.000h (L70B50) recessed Ø 198/228mm

Version with black or high gloss oxidised smooth optics on request

Code	Gear	Kg	Watt	Base	Lamps	Colour
22118317-12	CLD CELL-D	1,83	LED COB 51W	-	4500lm-3000K - 90°-CRI 90	WHITE
22118318-12	CLD CELL-D	1,85	LED COB 51W	-	4500lm-3000K - 60°-CRI 90	WHITE
22118319-12	CLD CELL-D	1,90	LED COB 51W	-	4500lm-3000K - 38°-CRI 90	WHITE
22118817-12	CLD CELL-D	1,68	LED COB 42W	-	3600lm-3000K - 90°-CRI 90	WHITE
22118818-12	CLD CELL-D	1,72	LED COB 42W	-	3600lm-3000K - 60°-CRI 90	WHITE
22118819-12	CLD CELL-D	1,63	LED COB 42W	-	3600lm-3000K - 38°-CRI 90	WHITE



Presence and light sensor