Fosnova

Office 1 Dark

A family of fixtures designed to combine high energy saving with excellent light quality, to address diverse needs concerning both safety and maintenance. The fixture's design is extremely clean and functional. Manufactured in accordance with standards EN12464 for VDT
Housing: Vandal-resistant, V2 self-extinguishing, UV-stabilized, anti-yellowing polycarbonate.
Reflector: V2 self-extinguishing polycarbonate; aluminium powder coated through a C.V.D. hard-vacuum process for greater light control and efficiency.
Equipment: Includes stainless steel springs ensuring perfect adherence to 1 to 20 mm. thick false ceilings
Regulations: Manufactured in accordance with standards EN60598 – CEI 34 –21. Degree of protection in accordance with standards EN60529.
LED 2000/3000
Luminous flux maintenance 70%: 60.000h (L70B10).
LED COB
Power factor: >0,95
Luminous flux maintenance 80%: 50.000h (L80B20).
Photobiological safety class: exempt group EN62471.

EL
EM
CLD
IK07
v.a. IP20
v.l. IP40
DIMM DIG
CLD-DD (DALI)
CLD D
CLD D-D-E
CLD E
RG0
Colour quality
LOW FLICKER
A+B=

Download

DXF 2D
- offi12.dxf

Montaggi
- OFFICE_1_rev5.pdf

BIM
- Office 1 Dark - 20200714.zip

Code	Gear	Kg	Lumen Output-K-CRI	WTot	Colour
22152371-00	CLD	0.90	LED 2000-1888lm-3000K-CRI 80	20 W	SILVER
22152375-00	CLD	1.70	LED 2000-2076lm-4000K-CRI 80	20 W	SILVER
22152372-00	CLD	1.60	LED 3000-2770lm-3000K-CRI 80	27 W	SILVER
22152374-00	CLD	1.70	LED 3000-3047lm-4000K-CRI 80	27 W	SILVER
22152371-1241	CLD-D-D	1.40	LED 2000-1888lm-3000K-CRI 80	20 W	SILVER
22152375-1241	CLD-D-D	1.60	LED 2000-2076lm-4000K-CRI 80	20 W	SILVER
22152372-1241	CLD-D-D	1.63	LED 3000-2770lm-3000K-CRI 80	27 W	SILVER
22152374-1241	CLD-D-D	1.80	LED 3000-3047lm-4000K-CRI 80	27 W	SILVER
22152371-9441	CLD-D-D-E	1.90	LED 2000-1888lm-3000K-CRI 80	20 W	SILVER
22152375-9441	CLD-D-D-E	2.15	LED 2000-2076lm-4000K-CRI 80	20 W	SILVER
22152372-9441	CLD-D-D-E	1.49	LED 3000-2770lm-3000K-CRI 80	27 W	SILVER
22152374-9441	CLD-D-D-E	2.10	LED 3000-3047lm-4000K-CRI 80	27 W	SILVER
22152370-00	CLD	0.90	LED COB-2782lm-3000K-CRI>90	31 W	SILVER
22152373-00	CLD	0.91	LED COB-2916lm-4000K-CRI>90	31 W	SILVER
22152376-00	CLD	0.92	LED COB-3325lm-3000K-CRI>90	38 W	SILVER
22152377-00	CLD	0.91	LED COB-3486lm-4000K-CRI>90	38 W	SILVER
22152370-1241	CLD-D-D	1.40	LED COB-2782lm-3000K-CRI>90	31 W	SILVER
22152373-1241	CLD-D-D	0.97	LED COB-2916lm-4000K-CRI>90	31 W	SILVER
22152376-1241	CLD-D-D	0.99	LED COB-3325lm-3000K-CRI>90	38 W	SILVER
22152377-1241	CLD-D-D	2.00	LED COB-3486lm-4000K-CRI>90	38 W	SILVER
22152370-9441	CLD-D-D-E	2.00	LED COB-2782lm-3000K-CRI>90	31 W	SILVER
22152373-9441	CLD-D-D-E	1.52	LED COB-2916lm-4000K-CRI>90	31 W	SILVER
22152376-9441	CLD-D-D-E	2.00	LED COB-3325lm-3000K-CRI>90	38 W	SILVER
22152377-9441	CLD-D-D-E	2.00	LED COB-3486lm-4000K-CRI>90	38 W	SILVER

The reported luminous flux is the flux emitted by the light source with a tolerance of ± 10% compared to the indicated value. The W tot column indicates the total wattage absorbed by the system without exceeding 10% of the indicated

Accessories

Accessories

- Presence and light sensor

- EM Kit R

The reported luminous flux is the flux emitted by the light source with a tolerance of ± 10% compared to the indicated value. The W tot column indicates the total wattage absorbed by the system without exceeding 10% of the indicated