



Download DXF 2D - offi12.dxf Montaggi - OFFICE_1_rev5.pdf



Office 1 Dark - Tunable white

A family of fixtures designed to combine high energy saving with excellent light quality, to address diverse needs concerning both safety and maintenance. The fixture's design is extremely clean and functional. Manufactured in accordance with standards EN12464 for VDT

Housing: Vandal-resistant, V2 self-extinguishing, UV-stabilized, anti-yellowing polycarbonate.

Reflector: V2 self-extinguishing polycarbonate; aluminium powder coated through a C.V.D. hard-vacuum process for greater light control and efficiency. Equipment: Includes stainless steel springs ensuring perfect adherence to 1 to 20 mm. thick false ceilings

Regulations: Manufactured in accordance with standards EN60598 - CEI 34 –21. Degree of protection in accordance with standards EN60529.

-21. Degree or protection in accordance with standards Enous29.
Photobiological safety class: exempt group EN62471.
Tunable White system for Downlights with adjustable colour temperature from 2,700 to 6,500 K at constant luminous flux. Ideal for retail, public spaces (hotels and restaurants), corridors, stairs, applications.
Functions: Constant light output function (CLO) • switchDIM and colourSWITCH with memory function; • colourSWITCH with 9 predefined

colours; · Configurable via DALI;

min 135 max 146		
	Ø220	
110	Ø220	

Code	Gear	Kg	Lumen Output-K-CRI	WTot	Colour
22152378-00	CLD-D-D	1,07	LED COB-3000lm-2700-6500K-CRI>90	31 W	SILVER

Ø190-215

The reported luminous flux is the flux emitted by the light source with a tolerance of ± 10% compared to the indicated value. The W tot column indicates the total wattage absorbed by the system without exceeding 10% of the indicated