



69

=

ഗ

7

100

## Download DXF 2D

- 175310.dxt



1 Ø82x82

100

80

8

## JF 2 mini square

Family of recessed spotlights, available in round profiles, which is particularly JF LED significantly improves the management of the store itself with all the advantages of LED sources.

Light is softer and improves comfort creating spaces that are more pleasant to live in and that make shopping even more enjoyable.

All spotlights have optics in polished aluminium for high efficiency and excellent glare control. Ideal for spaces where light runs all day long (malls, hotels, showrooms).

Housing: in die cast aluminium with glass

Reflector: dark light optics in high gloss, anti-glare aluminium to optimise light efficiency.

Installation: is equipped with galvanised steel support brackets, with housing for springs for attachment to the false ceilings. Painting: dust painted, using polyester epoxy paint to withstand UV rays. Standard supply: Includes adjustable steel bracket. Regulations: Manufactured in accordance with standards EN60598 – CEI 34

-21. Degree of protection in accordance with standards EN60529. LED: high-efficiency light sources 1055lm - 16W - 3000K - 70° - CRI 80

Power factor: 0.9

Photobiological safety class: Exempt group. Luminous flux maintenance 70%: 30.000h (L70B50). recessed Ø 75/90mm

on request matt glass version

	100		<b>55</b>			
Code	Gear	Kg	Watt	Base	Lamps	Colour
22175310-00	CLD CELL	0,40	LED COB 13W	-	1055lm-3000K - 70°-CRI>80	WHITE

21	10	5/2	01	4
21	10	312	:U I	0