



Store 2 - CDM-R

The STORE a new beam optic unit has been created with CDM and/or AR111 lamps.

Installation has been improved too, by a springs system, making recessed installation faster and easier.

Coating: Fluid-coated with a humidity resistant, UV-stabilised acrylic-resin paint, interior part is black and the border is white .

Lampholder: Ceramic with silver-plated contacts.

Electric gear: Equipped without transformer and silicon cable, cross section 0.75 mm².

Equipment: Supplied with springs ensuring perfect adherence to 1 to 25 mm thick false ceilings.

Terminal block: maximum allowed lead cross section 1,5mm²

Lamp: Complete with halogen lamps and/or ceramic metal halide lamp.

Regulations: Manufactured in accordance with EN 60598-1-CEI 34-21 standards. Degree of protection in accordance with EN60529 standard.

Download

DXF 2D
- 181413.dxf

Code	Gear	Kg	Lumen-K-CRI	WTot	Base	Colour
22181413-00	CELL	2.45	CDM-R111 3x70-2850lm-3000K-Ra 1b	160 W	Gx8.5	WHITE
22181475-00	CELL	2.45	CDM-R111 3x70-2850lm-3000K-Ra 1b CDM-R111 3x70-2850lm-3000K-Ra 1b	160 W	Gx8.5 Gx8.5	SILVER

The reported luminous flux is the flux emitted by the light source with a tolerance of ± 10% compared to the indicated value. The W tot column indicates the total wattage absorbed by the system without exceeding 10% of the indicated