

Focus - base

This version features a particular shape and a design with clean lines that can meet different architectonic lighting needs using high colour rendering LEDs. It is an all-new spotlight, which is entirely adjustable for an extraordinarily effective lighting project that adds value to any space and object

Housing: in die-cast aluminium with anodised heat sink.

Version with reflector: in die-cast polished aluminium, high efficiency and anti-glare.

Coating: UV-resistant acrylic resin powder coating.


Standard: manufactured pursuant to EN 60598-1-CEI 34.21 and with a degree of protection pursuant to EN 60529.

on request: 31° - 52°

Luminous flux maintenance 50.000h (L80B20).

Power factor >0.95

Photobiological safety class: exempt group EN62471.



Download

DXF 2D
- matfocusbas.dxf

3DS
- fosnova_matrix_focus.3ds

3DM
- fosnova_matrix_focus.3dm

Montaggi
- FOCUS rev6.pdf

Code	Gear	Kg	Lumen Output-K-CRI	WTot	Colour
22203410-00	CLD CELL-D	1.50	LED COB-2536lm-3000K-44°-CRI 92	26 W	WHITE
22203430-00	CLD CELL-D	1.48	LED COB-2536lm-3000K-44°-CRI 92	26 W	BLACK
22203470-00	CLD CELL-D	1.48	LED COB-2536lm-3000K-44°-CRI 92	26 W	SILVER
22203412-00	CLD CELL-D	1.30	LED COB-3842lm-3000K-44°-CRI 92	39 W	WHITE
22203432-00	CLD CELL-D	1.30	LED COB-3842lm-3000K-44°-CRI 92	39 W	BLACK
22203472-00	CLD CELL-D	1.50	LED COB-3842lm-3000K-44°-CRI 92	39 W	SILVER
22203414-00	CLD CELL-D	1.46	LED COB-4295lm-3000K-44°-CRI 92	45 W	WHITE
22203434-00	CLD CELL-D	1.48	LED COB-4295lm-3000K-44°-CRI 92	45 W	BLACK
22203474-00	CLD CELL-D	1.50	LED COB-4295lm-3000K-44°-CRI 92	45 W	SILVER
22203416-00	CLD CELL-D	1.56	LED COB-4897lm-3000K-44°-CRI 92	53 W	WHITE
22203436-00	CLD CELL-D	1.47	LED COB-4897lm-3000K-44°-CRI 92	53 W	BLACK
22203476-00	CLD CELL-D	1.48	LED COB-4897lm-3000K-44°-CRI 92	53 W	SILVER
22203410-1241	CLD CELL-D-D	1.50	LED COB-2536lm-3000K-44°-CRI 92	26 W	WHITE
22203430-1241	CLD CELL-D-D	1.48	LED COB-2536lm-3000K-44°-CRI 92	26 W	BLACK
22203470-1241	CLD CELL-D-D	1.48	LED COB-2536lm-3000K-44°-CRI 92	26 W	SILVER
22203412-1241	CLD CELL-D-D	1.48	LED COB-3842lm-3000K-44°-CRI 92	39 W	WHITE
22203432-1241	CLD CELL-D-D	1.30	LED COB-3842lm-3000K-44°-CRI 92	39 W	BLACK
22203472-1241	CLD CELL-D-D	1.49	LED COB-3842lm-3000K-44°-CRI 92	39 W	SILVER
22203414-1241	CLD CELL-D-D	1.46	LED COB-4295lm-3000K-44°-CRI 92	45 W	WHITE
22203434-1241	CLD CELL-D	1.48	LED COB-4295lm-3000K-44°-CRI 92	45 W	BLACK
22203474-1241	CLD CELL-D-D	1.55	LED COB-4295lm-3000K-44°-CRI 92	45 W	SILVER
22203416-1241	CLD CELL-D-D	1.48	LED COB-4897lm-3000K-44°-CRI 92	54 W	WHITE
22203436-1241	CLD CELL-D-D	1.49	LED COB-4897lm-3000K-44°-CRI 92	54 W	BLACK
22203476-1241	CLD CELL-D-D	1.48	LED COB-4897lm-3000K-44°-CRI 92	53 W	SILVER
22203410-68	CLD CELL-D	1.46	LED COB-4897lm-3000K-44°-CRI 92	28 W	WHITE
22203430-68	CLD CELL-D	1.48	LED COB-4897lm-3000K-44°-CRI 92	26 W	BLACK
22203470-68	CLD CELL-D	1.46	LED COB-4897lm-3000K-44°-CRI 92	26 W	SILVER
22203412-68	CLD CELL-D	1.47	LED COB-4111lm-4000K-44°-CRI 92	39 W	WHITE
22203432-68	CLD CELL-D	1.30	LED COB-4111lm-4000K-44°-CRI 92	39 W	BLACK
22203472-68	CLD CELL-D	1.50	LED COB-4111lm-4000K-44°-CRI 92	39 W	SILVER
22203414-68	CLD CELL-D	1.56	LED COB-4596lm-4000K-44°-CRI 92	45 W	WHITE
22203434-68	CLD CELL-D	1.48	LED COB-4596lm-4000K-44°-CRI 92	45 W	BLACK

The reported luminous flux is the flux emitted by the light source with a tolerance of ± 10% compared to the indicated value. The W tot column indicates the total wattage absorbed by the system without exceeding 10% of the indicated

Focus - base

Code	Gear	Kg	Lumen Output-K-CRI	WTot	Colour
22203474-68	CLD CELL-D	1.50	LED COB-4596lm-4000K-44°-CRI 92	45 W	SILVER
22203416-68	CLD CELL-D	1.50	LED COB-5240lm-4000K-44°-CRI 92	53 W	WHITE
22203436-68	CLD CELL-D	1.47	LED COB-5240lm-4000K-44°-CRI 92	53 W	BLACK
22203476-68	CLD CELL-D	1.49	LED COB-5240lm-4000K-44°-CRI 92	54 W	SILVER
22203410-6841	CLD CELL-D-D	1.48	LED COB-2713lm-4000K-44°-CRI 92	26 W	SILVER
22203430-6841	CLD CELL-D-D	1.48	LED COB-2713lm-4000K-44°-CRI 92	26 W	BLACK
22203470-6841	CLD CELL-D-D	1.48	LED COB-2713lm-4000K-44°-CRI 92	26 W	SILVER
22203412-6841	CLD CELL-D-D	1.48	LED COB-4111lm-4000K-44°-CRI 92	39 W	WHITE
22203432-6841	CLD CELL-D-D	1.30	LED COB-4111lm-4000K-44°-CRI 92	39 W	BLACK
22203472-6841	CLD CELL-D-D	1.49	LED COB-4111lm-4000K-44°-CRI 92	39 W	SILVER
22203414-6841	CLD CELL-D-D	1.46	LED COB-4596lm-4000K-44°-CRI 92	45 W	WHITE
22203434-6841	CLD CELL-D-D	1.48	LED COB-4596lm-4000K-44°-CRI 92	45 W	BLACK
22203474-6841	CLD CELL-D-D	1.50	LED COB-4596lm-4000K-44°-CRI 92	45 W	SILVER
22203416-6841	CLD CELL-D-D	1.48	LED COB-5240lm-4000K-44°-CRI 92	54 W	WHITE
22203436-6841	CLD CELL-D-D	1.49	LED COB-5240lm-4000K-44°-CRI 92	54 W	BLACK
22203476-6841	CLD CELL-D-D	1.57	LED COB-5240lm-4000K-44°-CRI 92	53 W	SILVER

The reported luminous flux is the flux emitted by the light source with a tolerance of $\pm 10\%$ compared to the indicated value. The W tot column indicates the total wattage absorbed by the system without exceeding 10% of the indicated