

Download DXF 2D rios.dxf Montaggi - RIO rev7.pdf



Fosnova

## Rio - base version

This floodlight's special design represents an effective complement to the decoration of the interior in which it is installed.

Ideal for commercial premises where lighting is used for many hours a day, or in areas characterised by high-quality, stable-colour functional and accent lighting.

Housing: in die-cast aluminium.

Reflector: in die-cast polished aluminium, high efficiency and anti-glare. Standard supply: mounted versions.

Coating: Power-coated with a UV-resistant polyester epoxy pain.

Regulations: Manufactured in accordance with EN 60598-1-CEI 34.21 standards. Degrees of protection in accordance with EN60529 standards. Luminous flux maintenance 80%: 50.000h (L80B20). Power factor >0.9

Photobiological safety class: exempt group EN62471. On request: version with CASAMBI advanced home automation lighting control system (max. 40W).



	-				
Code	Gear	Kg	Lumen Output-K-CRI	WTot	Colour
22206010-00	CLD-D	1.75	LED COB-3877lm-3000K-45°-CRI>90	39 W	WHITE
22206070-00	CLD-D	1.70	LED COB-3877lm-3000K-45°-CRI>90	39 W	SILVER
22206030-00	CLD-D	1.68	LED COB-3877Im-3000K-45°-CRI>90	39 W	BLACK
22206011-00	CLD-D	1.70	LED COB-4148lm-4000K - 45°-CRI>90	39 W	WHITE
22206031-00	CLD-D	1.68	LED COB-4148Im-4000K - 45°-CRI>90	39 W	BLACK
22206071-00	CLD-D	1.75	LED COB-4148Im-4000K - 45°-CRI>90	39 W	SILVER
22206013-00	CLD-D	1.85	LED COB-4937lm-3000K-45°-CRI>90	53 W	WHITE
22206033-00	CLD-D	1.71	LED COB-4937lm-3000K-45°-CRI>90	53 W	BLACK
22206073-00	CLD-D	1.70	LED COB-4937lm-3000K-45°-CRI>90	53 W	SILVER
22206014-00	CLD-D	1.68	LED COB-5309lm-4000K-45°-CRI>90	53 W	WHITE
22206034-00	CLD-D	1.71	LED COB-5309lm-4000K-45°-CRI>90	53 W	BLACK
22206074-00	CLD-D	1.68	LED COB-5309lm-4000K-45°-CRI>90	53 W	SILVER

The reported luminous flux is the flux emitted by the light source with a tolerance of ± 10% compared to the indicated value. The W tot column indicates the total wattage absorbed by the system without exceeding 10% of the indicated