


Download

DXF 2D
- sevilla3.dxf
Montaggi
- sevilla123.pdf



Sevilla 3 - 220/240V

Body / Frame: in pressed aluminum. Diffuser: In tempered glass th. 4mm resistant to thermal shocks and impacts. Equipment: complete with galvanized and painted bracket, with electric cable L = 0.6m. LED: power factor: 0.9. Luminous flux maintenance at 80%: 50.000h (L80B20). Photobiological risk classification: exempt group



Code	Gear	Kg	Lumen Output-K-CRI	WTot	Colour
22413531-00	CLD	1,28	LED-9200-3000K-CRI 80	90 W	GRAPHITE
22413532-00	CLD	1,29	LED-9900-4000K-CRI 80	90 W	GRAPHITE
22413533-00	CLD	1,29	LED-9900-6500K-CRI 80	90 W	GRAPHITE
22413531-19	CLD	1,28	LED-9200-3000K-CRI 80	90 W	GRAPHITE
22413532-19	CLD	1,29	LED-9900-4000K-CRI 80	90 W	GRAPHITE
22413533-19	CLD	1,29	LED-9900-6500K-CRI 80	90 W	GRAPHITE

The reported luminous flux is the flux emitted by the light source with a tolerance of $\pm 10\%$ compared to the indicated value. The W tot column indicates the total wattage absorbed by the system without exceeding 10% of the indicated