

info@fosnova.it - http://www.fosnova.it

| | 9 3 - LED | $\begin{array}{c} 121 \\ 63 \\ 737 \\ 7 \\ 737 \\ 7 \\ 7 \\ 7 \\ 7 \\ 7 \\ $ | | KOT 📩 🛠 🖡 | ₩ 📽 🛍 🕅 🥵 💥 CE |
|-------------|------------|--|---------------------|-----------|--------------------------------|
| Code | Gear | Kg Colour | Dimensions | W Tot | lamp |
| 22710974-00 | CLD CELL-F | 0.90 met. silv | er 131x140x125Ø125 | 8 | POWERLED white-540Im-3000K-10° |
| 22710976-00 | CLD CELL-F | 0.90 met. silv | er 131x140x125 Ø125 | 8 | POWERLED white-645Im-6000K-10° |

Housing: Die cast aluminium with openable frame designed with bayonet coupling to allow easy lamp maintenance.

Painting: Acrylic resin based UV resistant powder paint.

Equipment: supplied complete with adjustable bracket (on vertical axis with 355° rotation) in die cast aluminium providing internal passage for wires.

Standards: Products comply with EN 60598-1-CEI 34.21 standards, with level of protection in accordance with EN 60529 standards.

Complete with 1 module PowerLed 3X2.5W - 3000/6000K - 10°