




### 3116 Ghost LED – Diffuser with micro-satin finish

Housing: In die-cast aluminium, with wide cooling fins.  
 Diffuser: In clear polycarbonate. Prismatic inside for better light control. Smooth outside, dust-proof, impact-resistant, vandal-resistant, V2 self-extinguishing and UV stabilised.  
 Coating: Multistage process. Stage 1: gris epoxy cationic electrocoating, resistant to corrosion and briny mist. Stage 2: UV-stabilising priming. Stage 3: metallised silver acrylic finishing.  
 Standard supply: Removable gear tray.  
 Equipment: Suspension hook. Rubber cable gland Ø ½" gas thread (cable min Ø 9, max Ø12).  
 Regulations: Produced according to applicable EN60598-1 CEI 34 - 21 standards. IP43IK08 degree of protection according to EN 60529 standards. This product can be installed on normally inflammable surfaces.  
 LED: Latest generation LED technology, Ta-30 + 40°C life 50.000h to 80% L80B20  
 Photobiological safety class: exempt group EN62471.



Code	Gear	Kg	Lumen Output-K-CRI	WTot	Colour
322928-00	CLD	3.33	LED-2661lm-4000K-CRI 90	28 W	GREY9007
322929-00	CLD	3.01	LED-3697lm-4000K-CRI 90	38 W	GREY9007

**Download**  
 DXF 2D  
 - 3116.dxf  
 BIM  
 - 3116 Ghost LED – Diffuser with  
 micro-satin finish - 20200611.zip

The reported luminous flux is the flux emitted by the light source with a tolerance of ± 10% compared to the indicated value. The W tot column indicates the total wattage absorbed by the system without exceeding 10% of the indicated