

**IP43**

**Download**


DXF 2D  
- 3120\_1\_2.dxf

Montaggi  
- ghostcan.dxf  
- 3120\_1.dxf  
- ap\_diff.dxf  
- ghostcat.dxf  
- ghostcat.dxf  
- 3110-11-12-13-14-20-21-22-23-24\_ghost.pdf




**3121 Ghost - metallic internal diffuser**

**Housing:** In die-cast aluminium, with wide cooling fins.  
**Diffuser:** All in clear polycarbonate. Prismatic inside for better light control. Smooth outside, dust-proof and impact-resistant, V2 self-extinguishing and UV stabilised. The reflector is metallized inside with a C.V.D. high vacuum process using high grade aluminium powders for higher efficiency.  
**Coating:** Multistage process. Stage 1: gris epoxy cationic electrocoating, resistant to corrosion and briny mist. Stage 2: UV-stabilising priming. Stage 3: sandblasted silver acrylic finishing.  
**Lampholder:** In ceramics, with silver-plated or polycarbonate contacts.  
**Electric gear:** 230V/50Hz power supply. Silicone flexible wire terminated with quick-connect admiralty brass clamps, with fibreglass braid, 1.5 sqmm cross-section. 2P+T terminal block with maximum allowed lead cross section of 2,5 sqmm.  
**Equipment:** Suspension hook. Rubber cable gland Ø ½" gas thread (cable min Ø 9, max Ø12).  
**Regulations:** Produced according to applicable EN60598-1 CEI 34 - 21 standards, it has been granted the ENEC European Certificate of Conformity. IP43IK08 degree of protection according to EN 60529 standards. This product can be installed on normally inflammable surfaces.



Code	Gear	Kg	Lumen-K-CRI	WTot	Base	Colour
323037-00	CNR-L	6.74	JM-E 150-13300lm-3200K-Ra 1b	157 W	E27	GREY9007
323035-00	CNR-L	6.74	CDO-TT 150-13500lm-2800K-Ra 1b	157 W	E40	GREY9007

**Accessories**



The reported luminous flux is the flux emitted by the light source with a tolerance of ± 10% compared to the indicated value. The W tot column indicates the total wattage absorbed by the system without exceeding 10% of the indicated