



3221 Sforza LED asymmetric

Urban elegance often rhymes with simplicity. A need is felt for simple and easily recognizable shapes in an urban landscape increasingly crowded with stimuli and confused signals.

Sforza conveys a sense of peace and reliability, which is just what a good urban lighting project requires. (also indoor version)

Housing/Frame: in die-cast aluminium. With provision for central connection. Optics: in high-efficiency, metal-coated V0 polycarbonate, matt finish and micro-facetted to reduce direct glare.

Diffuser: tempered glass, 5 mm thick, thermal shock and impact resistant (UNI EN 12150 tests .- 1/2001).

Coating: in different stages. By epoxy cationic electrocoating, resistant to corrosion and saline environments. Second coating using sand-blasted silver coloured and graphite grey acrylic resin, green, UV stabilized. Additional colours are available upon request.

Equipment: device for automatic temperature control. In the event of an unexpected LED temperature rise caused by particular weather conditions or a LED failure, the system will reduce the luminous flux to lower the working temperature and guarantee proper operation. Complete with quick connection. Standard knife switch.


LED 4000K - 530mA - 10800lm - 72W - CRI>70. Latest generation LED technology, Ta-30+40°C life 60.000h L70B20 Photobiological safety class: exempt group

The total return of the equipment is close to 100%. Each LED module is equipped with a lens with high efficiency

Regulations: Produced according to applicable EN60598-1 CEI 34-21 standards, degree of protection according to EN 60529 standards.

Download DXF 2D

- 3221.dxf 3DS - disano_3221_sforza.3ds 3DM - disano_3221_sforza.3dm Montaggi - sforza2.pdf - sforza forcella installazione.dxf



1435 Village Pole

Ø 500

Code	Gear	Kg	Watt	Base	Lamps		Colour	
327090-00	CLD CELL	14,00	LED white 72W	-	10800lm @ 530mA-4000K-CRI>70)	SILVER/GRAPHITE	
Pali								
	- 1430 City Pole		- 1481 tapered steel	lighting pole	- 1480 tapered steel lighting pole		- 1409 fluted pole ø100	
Ŷ	- 1477 Urban mast with base	•	- 1508 fluted pole ø1 base	120 with	- 1509 fluted pole ø120	0	- 1478 Urban to be sunk into the ground	