



Ø610

191

3310 Visconti 11 LED

Visconti is the new urban lighting system that enables designers to get the best performance from the new light sources LED, with all the quality of the 'made in Italy' design.

The fixture's exclusive design is enhanced with an innovative pole, which is a visible sign of the changes occurred in the new town planning and redevelopment projects.

In its LED version, Visconti is equipped with optics designed to obtain greater light intensity in different urban routes: roads for vehicles, walkways for pedestrians and green areas.

Visconti is best suited to illuminate main streets in residential centres. As a wall-mounted fixture, it is the perfect solution to establish a dialogue between classic and modern architecture, while the suspended version enables a calibrated and wise use of light.

All the experience and quality of Disano products lie in the materials and technology of its products combined with easy installation and maintenance. Housing/Frame: in die-cast aluminium.

Diffuser: tempered glass, 5 mm thick, thermal shock and impact resistant (UNI EN 12150 tests - 1/2001

Coating: in different stages. By epoxy cationic electrocoating, resistant to corrosion and saline environments. Second coating using graphite grey acrylic resin, UV stabilized.

Standard supply: complete with socket-plug. Device for automatic temperature control. In the event of an unexpected LED temperature rise caused by particular weather conditions or a LED failure, the system will reduce the luminous flux to lower the working temperature and guarantee proper operation. Supplied with double insulation switch that cuts off electricity when the cover is opened.

POWERLED 4000K - 530mA - 8100/10800lm - 54/72W (on request 350mA 5544/7392lm - 34/46W)

LED: Latest generation LED technology, Ta-30+40°C life 60.000h L70B20

Photobiological safety class: exempt group Regulations: Produced according to applicable EN60598-1 CEI 34-21 standards, degree of protection according to EN 60529 standards.

Code	Gear	Kg	Watt	Base	Lamps	Colour
328181-00	CLD CELL	12,98	LED white 72W	-	10800lm @ 530mA-4000K-CRI>70	GRAPHITE
328180-00	CLD CELL	13,14	LED white 54W		8100lm @ 530mA-4000K-CRI>70	GRAPHITE

Accessories			
- 1464 Corona	- 1465 flange ø120	- 14 celling mount ø 30	- 1473 bent arm
α δ β β β β β β β β β β β β β	- 384 pole connector 2x	- 385 pole connector 1x	- 511 bent arm
- 55 suspension mounting			
Posts			
- 1508 fluted pole ø120 with base	- 1509 fluted pole ø120	- 1491 poles to be sunk into the ground	- 1340 pole with base
- 1508 fluted pole σ120 with base - 1308 fluted pole σ120 with base - 1343 pole	1509 fluted pole ø120 1493 pole with base	- 1491 poles to be sunk into the ground	

3DM disano 3310 visconti 3dm

Download

DXF 2D

3DS

- 3310.dxf

Montaggi - visconti-3300-1-3-7-10.pdf

disano 3310 visconti.3ds