

### 3393 Sella 2 - Asymmetrical 60°



Housing and cover: in die-cast aluminium and designed with a very small surface exposed to wind. Cooling fins are integrated into the cover. Optics: in aluminium coated with very high purity (99.99%) silver using physical vapour deposition (PVD). Pole connection: in die-cast aluminium and with gaskets to secure the frame according to different inclinations. Adjustable ranges: between 0° and 20° for side mount; and between 0° and 20° for mast-top mounting. Inclination pace: 5°. Suited for poles with a diameter 42-76. Diffuser: extra-clear, tempered glass, 4 mm thick, resistant to thermal shock and impacts (UNI-EN12150-1: 2001). Coating: the standard powder coating consists of a first metal surface pre-treatment stage and of single layer of UV-stabilised, corrosion and salt resistant polyester powder coating. The SELLA luminaire is declared to have passed the 2000 hours of salt corrosion resistance test in accordance with ASTM B 117 standard and the 2000 hours of UV condensation test in accordance with the ASTM G 154 standard. Standard supply: double insulation switch that cuts off electricity when the cover is opened. Electronic safety device to protect the LED module and the related ballast compliant with EN 61547. External connector for quick installation. It works in two modes: - differential mode: surge between power cables and between the phase and neutral. - common mode: surge between power, L/N and ground cables or between the fixture's body if it is of class II and installed on a metal pole. Upon request: protection up to 10KV. Coating compliant with UNI EN ISO 9227 Corrosion tests in artificial atmospheres for aggressive environments.

Wind sAvailable upon request: - 1-10V dimmer: 10%-100% dimming with 1-10V device, to be ordered with subcode -12.

- Virtual midnight: stand-alone device with automatic flux reduction, to be ordered with subcode -30.

- Power line carrier: point-to-point diagnosis and control management system, to be ordered with subcode -0078.


- Wi-Fi remote control (to be agreed upon): point-to-point control and diagnosis system of the entire system with Wi-Fi technology.

- Nema Socket, subcode 40

- Zhaga Socket, subcode 0054

surface: 2640cm<sup>2</sup>.  
LED: Power factor: =0.92 maintenance of luminous flux at 80%: >100.000h (L80B10).

Registered Design DM/100271



catalogo.codice	catalogo.cablaggio	kg	catalogo.watt	catalogo.attacco	catalogo.lampade	catalogo.colore
330884-00	CLD CELL	10.90	LED		12260lm-700mA-4000K-CRI 70	GREY
330880-00	CLD CELL	10.90	LED		12260lm-700mA-4000K-CRI 70	GRAPHITE
330885-00	CLD CELL	11.24	LED		15325lm-700mA-4000K-CRI 70	GREY
330881-00	CLD CELL	11.30	LED		15325lm-700mA-4000K-CRI 70	GRAPHITE
330886-00	CLD CELL	11.74	LED		18390lm-700mA-4000K-CRI 70	GREY
330882-00	CLD CELL	11.62	LED		18390lm-700mA-4000K-CRI 70	GRAPHITE
330884-39	CLD CELL	10.94	LED		11402lm-700mA-3000K-CRI 70	GREY
330880-39	CLD CELL	10.90	LED		11402lm-700mA-3000K-CRI 70	GRAPHITE
330885-39	CLD CELL	11.24	LED		14252lm-700mA-3000K-CRI 70	GREY
330881-39	CLD CELL	11.30	LED		14252lm-700mA-3000K-CRI 70	GRAPHITE
330886-39	CLD CELL	11.74	LED		17103lm-700mA-3000K-CRI 70	GREY
330882-39	CLD CELL	11.62	LED		17103lm-700mA-3000K-CRI 70	GRAPHITE



**download**

DXF 2D  
- 3392-3393-3395.dxf

3DS  
- disano\_3393\_sella2\_24\_led.3ds  
- disano\_3393\_sella2\_20\_led.3ds  
- disano\_3393\_sella2\_16\_led.3ds

3DM  
- disano\_3393\_sella2\_20\_led.3dm  
- disano\_3393\_sella2\_16\_led.3dm  
- disano\_3393\_sella2\_24\_led.3dm

Montaggi  
- sella1-2.pdf