

Download

DXF 2D
- 1156fsi.dxf

3DS
- 1156_forum_fm.3ds


3DM
- 1156_forum_fm.3dm

Montaggi
- 1156 orient.dxf
- 1156-1186.pdf




1156 Forum - XS

Housing/frame: In die-cast aluminium, with cooling fins.
Reflector: In 99.98 aluminium, anodized and polished, with fin for recovery of unused light.
Diffuser: Tempered glass, 5 mm thick, resistant to thermal shocks and impacts. (UNI7142 tests, 3193 British standard).
Painting: With polyester powder, colour graphite, resistant to corrosive and saline environments.
Lampholder: In ceramics with silver-plated contacts. Cable socket.
Electric gear: 230V/50Hz (1000W) 400V/50Hz (2000W) power supply. Silicone wire terminated with clamps in admiralty brass, with fiberglass braid, 2.5 sqmm cross section. Nylon 2P+T terminal block with maximum allowed lead cross section of 6 sqmm.
Equipment: Cable gland in f.g. nylon Ø 1/2 gas thread. Protective device: when the back cover is opened (hinge opening), the normally closed contact opens and cuts off supply to the fixture. Aiming visor. Anticondensation filter. Standard igniter placed in a special box.
Regulations: Produced according to applicable EN60598-1 CEI 34-21 standards, IP66IK08 degree of protection according to EN 60529 standards. They have obtained the ENEC European Certificate of Conformity.
Additional gear: Hot restrike
Lamp: MAX-TS1000; MAX-TS2000.
Wind surface: L:1400cm² F:2000cm².
Hot restart with -99 subcode.



Code	Gear	Kg	Lumen-K-CRI	WTot	Base	Colour
412576-00	S	12,47	MAX-TS 1000 SA---	1060 W	by wire	GRAPHITE
412577-00	S	12,81	MAX-TS 2000 SA---	2085 W	by wire	GRAPHITE

Accessori



The reported luminous flux is the flux emitted by the light source with a tolerance of $\pm 10\%$ compared to the indicated value. The W tot column indicates the total wattage absorbed by the system without exceeding 10% of the indicated