














1131 Punto LED - COB



HOUSING: in die-cast aluminium with cooling fins.  
 REFLECTOR: in hammered pre-anodised 99.99 aluminium for LED versions.  
 DIFFUSER: tempered glass, 5 mm thick, resistant to thermal shock and impacts (UNI EN 12150-1:2001 tests) .  
 COATING: the standard powder coating consists of a first metal surface pre-treatment stage and of single layer of UV-stabilised, corrosion and salt resistant polyester powder coating.  
 STANDARD SUPPLY: complete with galvanised and coated bracket.  
 EQUIPMENT: during maintenance or lamp replacement, special safety rings keep the glass hooked to the housing.  
 REGULATORY STANDARD: manufactured pursuant to EN 60598 and a degree of protection IP65IK08 pursuant to EN 60529 tested after a 7 day accelerated ageing. Class of insulation I.  
 Wind surface: 300 cm<sup>2</sup>.  
 Ta-20+40°C life 50.000h to 80% L80B20  
 Power factor: 0.9.  
 Photobiological safety class: exempt group, EN62471  
 Wind surface: L:283cm<sup>2</sup> F:416cm<sup>2</sup>.

		IP65
		
		
	CLD CELL	IK08
		+40 C° -20
		RG0 Etrr

Download

Montaggi  
- punto2013.pdf

Code	Gear	Kg	Lumen Output-K-CRI	WTot	Colour	Surge
413750-00	CLD CELL	1.82	LED-2576lm-4000K-CRI 90	30 W	GRAFITE	1/2kV
413751-00	CLD CELL	1.84	LED-2576lm-4000K-CRI 90	30 W	GREY	1/2kV
413752-00	CLD CELL	1.98	LED-3161lm-4000K-CRI 90	43 W	GRAFITE	1/2kV
413753-00	CLD CELL	2.00	LED-3161lm-4000K-CRI 90	43 W	GREY	1/2kV

The reported luminous flux is the flux emitted by the light source with a tolerance of ± 10% compared to the indicated value. The W tot column indicates the total wattage absorbed by the system without exceeding 10% of the indicated