



1576 Square - direct or indirect light FS

Housing: in die-cast aluminium. Diffuser: in extra-clear tempered glass, 4 mm thick, thermal shock and impact resistant. Optics: in high-performance metallic V0 polycarbonate. Coating: the standard liquid immersion coating consists of a first metal surface pre-treatment stage, a successive epoxy cataphoresis corrosion and salt resistant coating, and a final layer of bi-component acrylic liquid UV-stabilised coating.
 Standard supply: supplied with plate for wall installation and cable with with airtight connector for mains connection. Luminous flux maintenance 80%: 50.000h (L80B20). Power factor 0.92
 Photobiological safety class: exempt group EN62471.
 Regulations: Produced according to applicable EN60598-1 CEI 34-21 standards, degree of protection according to EN 60529 standards. On request: DIMM 1/10 or DALI versions. Coating compliant with UNI EN ISO 9227 Corrosion tests in artificial atmospheres for aggressive environments.
 Mounting: rapid connection, the fixture does not need to be opened.

- Download**
- DXF 2D
- 1576.dxf
 - 3DS
- disano_1576_square.3ds
 - 3DM
- disano_1576_square.3dm
 - Montaggi
- square 04-21.pdf
 - BIM
- 1576 Square - direct or indirect light FS - 20200611.zip

Code	Gear	Kg	Lumen Output-K-CRI	WTot	Colour
420641-00	CLD	2.18	LED COB-2900lm-4000K-CRI 90	31 W	WHITE
420642-00	CLD	2.90	LED COB-2900lm-4000K-CRI 90	31 W	GRAPHITE
420644-00	CLD	2.20	LED COB-2697lm-3000K-CRI 90	31 W	WHITE
420645-00	CLD	2.22	LED COB-2697lm-3000K-CRI 90	31 W	GRAPHITE
420646-00	CLD	2.90	LED COB-1220lm-4000K-CRI 90	16 W	WHITE
420647-00	CLD	2.90	LED COB-1220lm-4000K-CRI 90	16 W	GRAPHITE
420648-00	CLD	2.14	LED COB-1135lm-3000K-CRI 90	16 W	WHITE
420649-00	CLD	2.18	LED COB-1135lm-3000K-CRI 90	16 W	GRAPHITE

The reported luminous flux is the flux emitted by the light source with a tolerance of ± 10% compared to the indicated value. The W tot column indicates the total wattage absorbed by the system without exceeding 10% of the indicated