


1731 Faro 3 - short version

Housing: In extruded aluminium, cylindrical section, Ø 180.
 Diffuser: In vandal resistant and V2 self-extinguishing clear polycarbonate, UV-stabilized. Louvre in anodized 99.85 aluminium.
 Painting: In several stages. First stage: black epoxy cationic electrocoating, upon chromate treatment, resistant to corrosive and saline environments. Second stage: UV-stabilizing primer, and lastly rough finish with gris coating.
 Lampholder: In white polycarbonate, with phosphor bronze contacts (FLC), socket G24q In ceramics with silver-plated contacts. Socket E27.
 Electric gear: 230-240V/50Hz power supply. Hard wire, 0.50 sqmm cross-section, PVC-HT sheath resistant up to 90°C, according to CEI 20-20 standard, or silicone flexible wire terminated with quick-connect clamps in admiralty brass, glass braid, 1.0 sqmm cross-section. 2P+T terminal block, maximum allowed lead cross-section of 4 sqmm.
 Standard supply: With base and anchor bolts to bury. Supplied with socket-pin connector for quick installation and air recycle valve
 Regulations: Produced according to applicable EN60598-1 CEI 34-21 standards, IP65IK10 degree of protection in compliance with EN 60529 standards. They have obtained ENEC European Certificate of Conformity. Non-polluting louvre, ideal for installation in zone 1 (UNI10819).

Download

- DXF 2D
- 1731i.dxf
- 3DS
- disano_1731_faro_3.3ds
- 3DM
- disano_1731_faro_3.3dm
- Montaggi
- faro_faro3_faro4_tn.pdf



| Code | Gear | Kg | Watt | Base | Lamps | Colour |
|-----------|-------|------|-------------|---------|--------------------|----------|
| 510010-08 | CELL | 3,62 | FLC 1x26T/E | Gx24q-3 | 1800lm-4000K-Ra 1b | GRAPHITE |
| 510011-00 | CNR-L | 4,80 | SAP-T 70 | E27 | 6000lm-2000K-Ra 4 | GRAPHITE |
| 510012-00 | CNR-L | 4,80 | JM-E 70 | E27 | 5300lm-4000k-Ra 1b | GRAPHITE |

Accessories



- 399 Connector for solid line