




**1849 Bitta 3 LED - floor version**

Apart from the purely functional purpose, outdoor lighting also has an aesthetic function. A lighting fixture with small dimensions and the proper light beam angle can create amazing and stylish light effects. This product was studied as a free-standing fixture equipped with a steel column or as a wall-mounted device. It also features great usage versatility and highly efficient and advanced technology for LED

Housing/Base: in die-cast aluminium.  
Diffuser: opal, shatterproof and self-extinguishing V2 polycarbonate, UV-stabilized.

Standard supply: version is complete with long bolts and socket-plug connector for quick installation.  
Working life: 40000 h (from -20° a +40° C - Ta=25°C).  
Regulations: Produced according to applicable EN60598-1 CEI 34-21 standards, degree of protection according to EN 60529 standards.



- Download**
- DXF 2D - 1849.dxf
  - 3DS - disano\_1849\_bitta\_3\_2400.3ds
  - 3DM - disano\_1849\_bitta\_3\_2400.3dm
  - Montaggi - bitta led 07-20.pdf
  - BIM
    - 1849 Bitta 3 - floor version - LED - Grey - 20200616.zip
    - 1849 Bitta 3 - floor version - LED - Corten - 20200616.zip
    - 1849 Bitta 3 - floor version - LED - Graphite - 20200616.zip
    - 1849 Bitta 3 - floor version - LED - Anthracite - 20200616.zip

Code	Gear	Kg	Lumen Output-K-CRI	WTot	Colour
511443-00	CLD	14.73	LED-2394lm-4000K-CRI>70	27 W	GREY9007
511444-00	CLD	14.23	LED-2394lm-4000K-CRI>70	27 W	GRAPHITE
511445-00	CLD	14.73	LED-2394lm-4000K-CRI>70	27 W	ANTHRACITE
511443-2191	CLD CELL	17.20	LED-2394lm-4000K-CRI>70	27 W	CORTEN

The reported luminous flux is the flux emitted by the light source with a tolerance of ± 10% compared to the indicated value. The W tot column indicates the total wattage absorbed by the system without exceeding 10% of the indicated