



1842 Bitta 1 - floor version - Design: Lorenzo Stano

Apart from the purely functional purpose, outdoor lighting also has an aesthetic function.

A lighting fixture with small dimensions and the proper light beam angle can create amazing and stylish light effects.

This product was studied as a free-standing fixture equipped with a steel column or as a wall-mounted device.

It also features great usage versatility and highly efficient and advanced technology

Housing/Base: in die-cast aluminium.

Diffuser: opal, shatterproof and self-extinguishing V2 polycarbonate, UV-stabilized.

Standard supply: version is complete with long bolts and socket-plug connector for quick installation.

Regulations: Produced according to applicable EN60598-1 CEI 34-21 standards, degree of protection according to EN 60529 standards.

Download

DXF 2D
- 1842.dxf

3DS
- disano_1842_bitta_1_600.3ds
- disano_1842_bitta_1_1100.3ds

3DM
- disano_1842_bitta_1_1100.3dm
- disano_1842_bitta_1_600.3dm

Montaggi
- bitta ground.dxf
- bitta.pdf

Code	Gear	Kg	Lumen-K-CRI	WTot	Base	Colour
511461-00	CELL	7.36	JM-TS 70-5700lm-4000k-Ra 1b	85 W	Rx7s	GRAPHITE
511462-00	CELL	7.36	JM-TS 70-6500lm-4200K-Ra 1b	85 W	Rx7s	ANTHRACITE
511465-00	CELL	6.36	FLC 2x26D/E-1800lm-4000K-Ra 1b	54 W	G24q-3	GREY9007
511466-00	CELL	6.36	FLC 2x26D/E-1800lm-4000K-Ra 1b	54 W	G24q-3	GRAPHITE
511467-00	CELL	6.36	FLC 2x26D/E-1800lm-4000K-Ra 1b	54 W	G24q-3	ANTHRACITE
511450-00	CELL	4.99	JM-TS 70-5700lm-4000k-Ra 1b	85 W	Rx7s	GREY9007
511451-00	CELL	4.99	JM-TS 70-5700lm-4000k-Ra 1b	85 W	Rx7s	GRAPHITE
511456-00	CELL	3.88	FLC 2x26D/E-1800lm-4000K-Ra 1b	54 W	G24q-3	GRAPHITE
511460-00	CELL	7.36	JM-TS 70-5700lm-4000k-Ra 1b	85 W	Rx7s	GREY9007
511455-00	CELL	3.88	FLC 2x26D/E-1800lm-4000K-Ra 1b	54 W	G24q-3	GREY9007
511457-00	CELL	3.88	FLC 2x26D/E-1800lm-4000K-Ra 1b	54 W	G24q-3	ANTHRACITE
511452-00	CELL	4.99	JM-TS 70-5700lm-4000k-Ra 1b	85 W	Rx7s	ANTHRACITE

The reported luminous flux is the flux emitted by the light source with a tolerance of ± 10% compared to the indicated value. The W tot column indicates the total wattage absorbed by the system without exceeding 10% of the indicated