



1849 Bitta 3 - floor version - Design: Lorenzo Stano

Apart from the purely functional purpose, outdoor lighting also has an aesthetic function.

A lighting fixture with small dimensions and the proper light beam angle can create amazing and stylish light effects.

This product was studied as a free-standing fixture equipped with a steel column or as a wall-mounted device.

It also features great usage versatility and highly efficient and advanced technology

Housing/Base: in die-cast aluminium.

Diffuser: opal, shatterproof and self-extinguishing V2 polycarbonate, UV-stabilized.

Standard supply: version is complete with long bolts and socket-plug connector for quick installation.

Regulations: Produced according to applicable EN60598-1 CEI 34-21 standards, degree of protection according to EN 60529 standards.

Download

DXF 2D
- 1842.dxf

Code	Gear	Kg	Lumen-K-CRI	WTot	Base	Colour
511480-00	CELL	14.53	JM-TS 70-5700lm-4000k-Ra 1b	85 W	Rx7s	GREY9007
511481-00	CELL	14.59	JM-TS 70-5700lm-4000k-Ra 1b	85 W	Rx7s	GRAPHITE
511482-00	CELL	14.53	JM-TS 70-5700lm-4000k-Ra 1b	85 W	Rx7s	ANTHRACITE
511483-00	CELL	14.57	FLC 2x26D/E-1800lm-4000K-Ra 1b	54 W	G24q-3	GREY9007
511484-00	CELL	14.57	FLC 2x26D/E-1800lm-4000K-Ra 1b	54 W	G24q-3	GRAPHITE
511485-00	CELL	14.57	FLC 2x26D/E-1800lm-4000K-Ra 1b	54 W	G24q-3	ANTHRACITE

The reported luminous flux is the flux emitted by the light source with a tolerance of $\pm 10\%$ compared to the indicated value. The W tot column indicates the total wattage absorbed by the system without exceeding 10% of the indicated