



1623 Starled - LED

Housing: Vandal resistant fibreglass nylon,.

Frame: Die-cast aluminium.

Diffuser: Frosted glass, resistant to impact and thermal shock .

Coating: the standard liquid immersion coating consists of a first metal surface pre-treatment stage, a successive epoxy cataphoresis corrosion and salt resistant coating, and a final layer of bi-component acrylic liquid UV-stabilised coating.

Electric gear: 24V 230V/50Hz power supply with external transformer acc.179.Wire insulation class 3.

Equipment: Rubber gasket.


Regulations: Manufactured in compliance with EN60598 - CEI 34 - 21 standards. The level of protection complies with EN 60529 standard.

Lamp: Supplied with LEDs other colours available on request). Separate transformer required (code 997665)

Download

DXF 2D
- 1623_powerled.dxf

Montaggi
- starled.dxf
- 1623montaggio.dxf



Code	Gear	Kg	Lumen Output-K-CRI	WTot	Colour
530694-00	CLD S+L	0,37	LED-84lm-4000K-	3 W	GRAPHITE
530695-00	CLD S+L	0,37	LED-84lm-4000K-	3 W	GREY9007
530695-2191	CLD S+L	0,00	LED-84lm-4000K-	3 W	CORTEN

Accessori



- 179 watertight box CC-IP677

The reported luminous flux is the flux emitted by the light source with a tolerance of $\pm 10\%$ compared to the indicated value. The W tot column indicates the total wattage absorbed by the system without exceeding 10% of the indicated