

Reflector LED - Forma

Reflector LED para la sustitución directa de los tubos fluorescentes presentes en el artículo Forma. ¡Mantiene tu luminaria de techo de acero y ahorra hasta el 50%!

LED

Factor de potencia: 0,9.

Eficiencia del módulo LED: 162 lm/W.

Flujo luminoso: 7060/9400lm

Índice de reproducción cromática: 80.

Mantenimiento del flujo luminoso al 80%: 50.000 h (L80B20).

Temperatura del color: 4000K.

Bajo pedido también 3000K y 6000K.



Download

Montaggi

- forma reflector.pdf

Code	Gear	Kg	Lumen-K-CRI	WTot
162445-16	CLD	1,60	LED-7060lm nominal flux-4000K-CRI>80	50 W
162446-16	CLD	2,00	LED-9400lm nominal flux-4000K-CRI>80	61 W

Prodotti



- 999 Forma T8 - acero



- 994 Forma T8 - acero + cristal



- 999 Forma T5 - acero



- 994 Forma T5 - acero + cristal



- 995 Forma LED - con vidrio grabado



- 993 Forma LED - vidrio transparente



- 983 Forma LED - sin ganchos para industria alimentaria

The reported luminous flux is the flux emitted by the light source with a tolerance of $\pm 10\%$ compared to the indicated value. The W tot column indicates the total wattage absorbed by the system without exceeding 10% of the indicated