



Download



Recessed springs

acc. 22001491-00 - 295x595 - 295x295 - 595x595

acc. 22001492-00 - 295x1185 Ideal for mounting the fixture in plasterboard false ceilings.

Code	Kg	WTot	Colour
22001491-00	0,19	0 W	ACIER
22001492-00	0,25	0 W	ACIER

Prodotti



- PanelTech UGR<19 - A



- Pannello B



- PanelTech High Performance -



- Eco Pannello luminoso



- PanelTech UGR<19 - B



- PanelTech UGR<19 - R2



- PanelTech UGR<19 - R3



- Eco Pannello luminoso R2



- PanelTech - PUSH DALI - UGR<19



- Eco Pannello luminoso - CAM



- Eco Pannello luminoso R2 - CAM



- Eco Pannello luminoso R4



- PanelTech High Performance - UGR<19 - A2 - CAM



- PanelTech High Performance - UGR<19 - R2 - CAM



- Pannello B - R2



- PanelTech High Performance - UGR<19 - R2



- Eco Pannello luminoso - architectural



- Eco Pannello luminoso 2x2 - UGR<19



- Eco Pannello luminoso 2x2

The reported luminous flux is the flux emitted by the light source with a tolerance of $\pm 10\%$ compared to the indicated value. The W tot column indicates the total wattage absorbed by the system without exceeding 10% of the indicated