

[Download](#)


Powered suspension with rods Q

Complete with power cord and rods. Max loading: 30Kg. Ø10 mm.

Code	Kg	WTot	Colour
22003175-00	0,28	0 W	ARGENT
22003116-00	0,42	0 W	BLANC
22003136-00	0,28	0 W	NOIR

Prodotti



- Omnitrack 3 allumages



- Omnitrack PLUS - DIMM - 6



- Sintesi System - suspension
lumière directe/indirecte -



- Sintesi System - suspensión -



- Sintesi System - suspensión
luz directa/indirecta - avec
diffuseur UGR<19



- Sintesi System - suspension -
optique Dark - UGR<19



- Sintesi System - suspension
lumière directe/indirecte -
optique Dark - UGR<19



- Sintesi System - suspension
avec diffuseur satiné - UGR<22



- Sintesi System - suspension
lumière directe/indirecte - avec
diffuseur satiné - UGR<22



- Sintesi System - plafond
asymétrique 25° - UGR<22



- Sintesi System - suspension
lumière directe/indirecte -
extensive 60° - UGR<22



- Sintesi System - suspension -
extensive

The reported luminous flux is the flux emitted by the light source with a tolerance of $\pm 10\%$ compared to the indicated value. The W tot column indicates the total wattage absorbed by the system without exceeding 10% of the indicated