



Pastilla - 100/240 V

Pastilla est un luminaire à LED haute performance, l'idéal pour remplacer les appareils traditionnels. L'étrier fourni simplifie l'installation de ce luminaire simple et moderne dans divers contextes, comme les couloirs, les escaliers, les halls ou espaces publics. Disponible en trois formats (ø220/280/330 mm), en version standard 3 000K/4 000K, ou sur demande avec cellule de luminosité-présence (ON-OFF). Corps : en polycarbonate incassable et auto-extinguible. Diffuseur : en polycarbonate, antiéblouissement, incassable et auto-extinguible. LED : Maintien du flux lumineux à 70%: 30.000h (L70B50). Facteur de puissance >0,9.

Download

DXF 2D

- past.dxf

Montaggi

- PASTILLA rev4.pdf

BIM

- Pastilla - 100-240 V - 20201005.zip

Code	Gear	Kg	Lumen Output-K-CRI	WTot	Colour
22042510-00	CLD	0,53	LED-1328lm-3000K-CRI 80	15 W	BLANC
22042511-00	CLD	0,55	LED-1444lm-4000K-CRI 80	15 W	BLANC
22042512-00	CLD	0,77	LED-1651lm-3000K-CRI 80	18 W	BLANC
22042513-00	CLD	0,79	LED-1796lm-4000K-CRI 80	18 W	BLANC
22042514-00	CLD	1,01	LED-2273lm-3000K-CRI 80	24 W	BLANC
22042515-00	CLD	1,02	LED-2473lm-4000K-CRI 80	24 W	BLANC
22042512-19	CLD	0,83	LED-1651lm-3000K-CRI 80	18 W	BLANC
22042513-19	CLD	0,83	LED-1796lm-4000K-CRI 80	18 W	BLANC
22042514-19	CLD	1,05	LED-2273lm-3000K-CRI 80	24 W	BLANC
22042515-19	CLD	1,08	LED-2473lm-4000K-CRI 80	24 W	BLANC
22042510-0050	CLD-EC	0,53	LED-1328lm-3000K-CRI 80	15 W	BLANC
22042511-0050	CLD-EC	0,53	LED-1444lm-4000K-CRI 80	15 W	BLANC
22042512-0050	CLD-EC	0,89	LED-1651lm-3000K-CRI 80	18 W	BLANC
22042513-0050	CLD-EC	0,80	LED-1796lm-4000K-CRI 80	18 W	BLANC
22042514-0050	CLD-EC	1,10	LED-2273lm-3000K-CRI 80	24 W	BLANC
22042515-0050	CLD-EC	1,01	LED-2473lm-4000K-CRI 80	24 W	BLANC

The reported luminous flux is the flux emitted by the light source with a tolerance of ± 10% compared to the indicated value. The W tot column indicates the total wattage absorbed by the system without exceeding 10% of the indicated