



Power supply series 24VDC 220-240V 50/60Hz

- Version constant current for Power LED - Screw terminals 1.5 mm² - Short circuit protection, overload, open circuit and thermal - High performance with minimum heat loss and absolute reliability - Compliance with EN61347-2-13 EN61347-1, EN62384, EN55015, EN61000-3-2, EN61547

Code	Cablage	Kg	Lumen-K-CRI	WTot
22090893-00	CLD	0.10		17 W
22090839-00	CLD	0.08	220-240V-24vDC 20W---	20 W
22092022-00	CLD	0.30		70 W

Produits



- Micro Liset - 4000K - CRI 80



- Micro Liset - IP65



- Micro Liset opal - 3000K - CRI



- Micro Liset - for solid line -



- Minilinea LED - en applique



- Micro Liset HO - 3000K - CRI 80



- Micro Liset - 3000K - CRI 92



- Micro Liset HO - 4000K - CRI 80



- Micro Liset - for solid line - 3000K - CRI 92



- Micro Liset TT



- Micro Liset HO - MEAT



- Micro Liset HO - BREAD



- Micro Liset HO - CHEESE



- Micro Liset HO - FRUIT



- Micro Liset HO - FISH



- Aosta LED



- Micro Liset HO - 6500K - CRI 80

Le flux lumineux mentionné est le flux lumineux sortant du luminaire, avec une tolérance de $\pm 10\%$ par rapport à la valeur indiquée. Les W totaux expriment la puissance totale consommée par le système avec une tolérance maximale de 10 %