



Download



Sospensione elettrificata - 5 poli

Completa di cavetto in acciaio (L = 100 cm) e cavo di alimentazione. Carico max.20Kg. Per cablaggio EM e DIMM DALI.

Code	Kg	WTot	Colour
22003121-00	0,62	0 W	NERO
22003120-00	0,61	0 W	BIANCO

Prodotti



- Slim 3 URG<19



- Liset 2.0 - a sospensione -



- Liset 2.0 - a sospensione - diretta/indiretta - Dark light -



- Liset 2.0 - a sospensione - diretta - ottiche comfort -



- Liset 2.0 - a sospensione - diretta/indiretta - ottiche comfort - UGR<19



- Liset 2.0 - a sospensione - luce diretta/indiretta - diffusore in policarbonato



- Liset 2.0 - C+2S



- Liset 2.0 - C+H+3M - UGR<19



- Liset 2.0 - C+M+2S - UGR<19



- Liset 2.0 - C+2M



- Liset 2.0 - C 4D



- Liset 2.0 - C 2D+2M



- Liset 2.0 - C 4M



- Liset 2.0 HE - sospensione luce diretta - UGR<19



- Liset 2.0 HE - sospensione luce diretta - biasimmetrico 25°



- Liset 2.0 HE - sospensione luce diretta - asimmetrico 25°



- Liset 2.0 HE - sospensione luce diretta - 90°



- Liset 2.0 - a sospensione - luce diretta - diffusore in policarbonato



- Liset 2.0 HE - sospensione luce diretta - 30°x80°

The reported luminous flux is the flux emitted by the light source with a tolerance of $\pm 10\%$ compared to the indicated value. The W tot column indicates the total wattage absorbed by the system without exceeding 10% of the indicated