

Serie alimentatore 24VDC 220-240V 50/60Hz

- Versione a tensione costante per moduli LED - Morsetti a vite 1,5mmq -
- Protezione al cortocircuito, sovraccarico, circuito aperto e termica - Elevato rendimento con minima dispersione di calore ed assoluta affidabilità nel tempo
- Conformità alle norme EN61347-2-13, EN61347-1, EN62384, EN55015, EN61000-3-2, EN61547

Download

Code	Gear	Kg	Lumen-K-CRI	WTot
22090893-00	CLD	0,10		17 W
22090839-00	CLD	0,08	220-240V-24vDC 20W---	20 W
22092022-00	CLD	0,30		70 W

Prodotti



- Micro Liset - 4000K - CRI 80



- Micro Liset - IP65



- Micro Liset opale - 3000K - CRI



- Micro Liset - fila continua -



- Minilinea LED - incasso a parete



- Micro Liset HO - 3000K - CRI 80



- Micro Liset - 3000K - CRI 92



- Micro Liset HO - 4000K - CRI 80



- Micro Liset - fila continua - 3000K - CRI 92



- Micro Liset TT



- Micro Liset HO - MEAT



- Micro Liset HO - BREAD



- Micro Liset HO - CHEESE



- Micro Liset HO - FRUIT



- Micro Liset HO - FISH



- Aosta LED



- Micro Liset HO - 6500K - CRI 80

The reported luminous flux is the flux emitted by the light source with a tolerance of $\pm 10\%$ compared to the indicated value. The W tot column indicates the total wattage absorbed by the system without exceeding 10% of the indicated