

Techno B 220 - TOTAL WHITE

Corpo: in alluminio pressofuso con schermo frontale in policarbonato trasparente.

Riflettore: ottica ossidata bianca.

Lente: in PMMA ad alta efficienza con bassissimo coefficiente di abbagliamento.

Equipaggiamento: Completo di staffa regolabile in acciaio.


Normativa: Prodotti in conformità alle norme EN 60598-1-CEI 34.21, hanno grado di protezione secondo le norme EN 60529.

LED: sorgenti luminose ad alta efficienza per una elevata qualità dei colori illuminati.

Mantenimento del flusso luminoso al 80%: 50.000h (L80B20).

Fattore di potenza ≥ 0.9

Classificazione rischio fotobiologico: gruppo esente.



| Code | Gear | Kg | Lumen Output-K-CRI | WTot | Colour |
|-------------|------|------|-----------------------------|------|--------|
| 22163312-00 | CLD | 1,53 | LED COB-4487lm-4000K-CRI 92 | 46 W | BIANCO |

Accessori



- EM Kit Q



Download

DXF 2D
- techno220.dxf

Montaggi
- TECHNO B rev3.pdf

The reported luminous flux is the flux emitted by the light source with a tolerance of $\pm 10\%$ compared to the indicated value. The W tot column indicates the total wattage absorbed by the system without exceeding 10% of the indicated