IP20 CLD IK07

Download

DXF 2D
- w9big.dxf



W9 Big FS - incasso

Moduli singoli installabili ad incasso a soffitto dalle dimensioni estremamente ridotte in modo da integrarsi perfettamente nell'ambiente. Questi moduli sono caratterizzati dall'ottica termoplastica ad alta definizione con finitura metallica, abbinata a uno speciale diffusore per ottimizzare l'emissione luminosa riducendo significativamente l'abbagliamento diretto.
A richiesta: disponibili versioni con diverse finiture estetiche ideali per creare suggestivi effetti di luce.
LED: Mantenimento del flusso luminoso al 80%: 50.000h (L80B20). Fattore di potenza: 0,92. Classificazione rischio fotobiologico: gruppo esente.
Normativa: Prodotti in conformità alle norme EN60598 - CEI 34 - 21. Hanno grado di protezione secondo le norme EN60529.



Code	Gear	Kg	Lumen Output-K-CRI	WTot	Colour
22190138-22	CLD	1,10	LED-2640lm-4000K-15°-CRI>90	36 W	NERO
22190138-3931	CLD	1,10	LED-2565lm-3000K-15°-CRI>90	36 W	NERO

The reported luminous flux is the flux emitted by the light source with a tolerance of ± 10% compared to the indicated value. The W tot column indicates the total wattage absorbed by the system without exceeding 10% of the indicated